

Hawea Wastewater Treatment Plant Annual Report 2018 - 2019

Prepared for

Queenstown Lakes District Council

Prepared by

L E W E
Environmental
I m p a c t

December 2019



Hawea Wastewater Treatment Plant Annual Report 2018-2019

Queenstown Lakes District Council

This report has been prepared for the **Queenstown Lakes District Council (QLDC)** by Lowe Environmental Impact (LEI). No liability is accepted by this company or any employee or sub-consultant of this company with respect to its use by any other parties.

| Quality Assurance Statement | | |
|-----------------------------|--|---|
| Task | Responsibility | Signature |
| Project Manager: | Melanie Burns | <i>Melanie Burns</i> |
| Prepared by: | Melanie Burns and Henry van der Vossen | <i>Henry van der Vossen</i> <i>Melanie Burns</i> |
| Reviewed by: | Rob Potts | |
| Approved for Issue by: | Brian Ellwood | <i>Brian Ellwood</i> |
| Status: | Final | |

Prepared by:

Lowe Environmental Impact
P O Box 29288
Christchurch 8540

| T | [+64] 3 359 3059
| E | office@lei.co.nz
| W | www.lei.co.nz

Ref: RE-QLDC-Hawea-WWTP-Annual-Report-2018-19-
Final.pdf

Job No.: 10229

Date: 19th December 2019



TABLE OF CONTENTS

| | | |
|----------|---|-----------|
| 1 | BACKGROUND | 1 |
| 2 | PURPOSE AND SCOPE OF REPORT | 3 |
| 3 | MONITORING REQUIREMENTS..... | 4 |
| 4 | WASTEWATER FLOWS AND SAMPLING | 5 |
| 4.1 | Wastewater Flows..... | 5 |
| 4.2 | Wastewater Sampling..... | 6 |
| 5 | NITROGEN MASS BALANCE..... | 12 |
| 5.1 | Mean Wastewater Nitrogen Concentration..... | 12 |
| 5.2 | Nitrogen Losses | 13 |
| 5.3 | LTA Nitrogen Loading (kg/ha)..... | 13 |
| 5.4 | Pasture Nitrogen Uptake and Cut & Carry Removal | 14 |
| 5.5 | Leached Nitrogen (kg/ha) from Spray Irrigation Area | 14 |
| 5.6 | Overall Annual Nitrogen Mass Balance for the Hawea WWTP | 14 |
| 6 | RESOURCE CONSENT REQUIREMENTS AND COMPLIANCE | 16 |
| 6.1 | Consent Compliance for 1 December 2018 to 30 th November 2019..... | 16 |
| 6.2 | Previous Consent Compliance | 23 |
| 6.3 | Progress Towards Compliance..... | 23 |
| 6.4 | Further Works to Transition to Compliance..... | 25 |
| 7 | SUMMARY AND CONCLUSIONS..... | 26 |
| 8 | REFERENCES | 28 |
| 9 | APPENDICES..... | 29 |

Appendix A Discharge Permits RM10.308.01 and RM10.308.02

Appendix B Wastewater Quality Monitoring Results

Appendix C Watercare Laboratory Results

Appendix D Daily Wastewater Flow Results

Appendix E Nitrogen Mass Balance Spreadsheet



Appendix F Maintenance Records

Appendix G Hawea River Water Sampling Results

Appendix H ERPRO (2019) QLDC Lake Hawea WWTP Nitrogen Reduction Implementation



1 BACKGROUND

The Hawea wastewater treatment plant (WWTP) comprising of an oxidation pond started operation in 1988 and treats wastewater originating from the Hawea township and the Timsfield subdivision. It is located adjacent to the true left bank of the Hawea River, approximately 600 metres south of the intersection of Domain Road and Cemetery Road (Figure 1.1). The legal description of the land parcel is Lot 1 DP 20555 and Lot 1 DP 24534. The map reference for the oxidation ponds is NZMS 260 G40: 128-137.



Figure 1.1: Hawea Township Reticulation

An upgrade to the discharge systems was made in 2010 when the overflow to the river was ceased, the trench disposal system enlarged (doubled in size) and a spray irrigation area was installed to reduce the nitrogen load entering groundwater and into the Hawea River. Discharge Permits RM10.308.01 and RM10.308.02 were issued by the Otago Regional Council (ORC) on the 15 November 2010. The consents are due to expire on the 12th November 2022.

Wastewater enters the oxidation pond (Figure 1.2) which is 1.2 m deep and 0.94 ha and maintained in an aerobic state with the use of three mechanical aerators. The volume of the pond is 10,250 m³ and has a hydraulic retention time of 50 days.

The wastewater is then discharged to land via either a spray irrigation system or a low-pressure disposal trench (Figure 1.2). The disposal trench is 150 metres long and 2 metres wide and is only meant to be used during periods when it is not suitable to use spray irrigation, that is when the soil is saturated, frozen, harvesting is occurring, or during periods of high wind speed. The disposal trench is to be used for a maximum of 4 months in any calendar year.

The land treatment area (LTA) on which treated wastewater is evenly applied by spray irrigation consists of a 2.33 hectares area planted with ryegrass. The LTA is also connected to a weather station that shuts it down in winds over 29.9 km/hr. The spray irrigation comprises of sprinklers on 1 m high risers with medium pressure lateral pipes at 20 m centres. The harvesting equipment drives around the risers during harvesting. The LTA is only used between the hours of 11 pm to 5 am due to the presence of an adjacent cycle/walking track (Figure 1.2).



Figure 1.2: Overview of Wastewater Treatment Plant

Veolia operates and maintains the oxidation ponds as part of the 3-Waters operations and maintenance contract.



2 PURPOSE AND SCOPE OF REPORT

The purpose of this report is to report to the Otago Regional Council (ORC) in accordance with Condition 13 of Resource Consent RM10.308.02 (Table 2.1) and covers the period 1 December 2018 to 30 November 2019.

The scope of the Annual Report comprises of the following:

- Summary of all analytical results for the year;
- Summary of the year's monitoring results and assessment against trigger levels in Resource Consent RM10.308.02, comparison against previous year's results;
- Nitrogen Mass Balance as required by Condition 12;
- Comments on compliance with the conditions of the discharge permits;
- Summary of any malfunctions or breakdowns and the corrective action taken;
- Summary of any complaints received, the validity of each complaint and the corrective action taken; and
- Any other issues considered relevant.

Table 2.1: Discharge Permits

| Consent Number | Description | Issue Date | Expiry Date | Reference |
|-----------------------|--|-------------------|--------------------|------------------|
| RM10.308.01 | To discharge contaminants to air for the purpose of discharging treated wastewater. | 15 Nov 2010 | 12 Nov 2022 | Appendix A |
| RM10.308.02 | To discharge contaminants to land for the purpose of discharging treated wastewater. | 15 Nov 2010 | 12 Nov 2022 | Appendix A |



3 MONITORING REQUIREMENTS

An overview of the monitoring requirements for Resource Consent RM10.308.02 is given in Table 3.1. The results of the wastewater quality monitoring for the 2018-2019 sampling period are presented in tabular format in Appendix B and a copy of the laboratory results received from Watercare Laboratories for the 2018-2019 period is presented in Appendix C. The wastewater flow results are presented in Appendix D.

Table 3.1: Wastewater Quality Parameters to be Analysed

| Parameter | Frequency | Resource Consent Trigger Level | Consent Conditions | Reporting Requirements |
|-------------------------|-----------|---|--------------------|------------------------|
| Flow (wastewater) | Daily | 775 cubic metres/day | 2, 9 | Annual |
| Total Nitrogen | Monthly* | Mean**: 35 mg/L 95 th percentile**: 40 mg/L | 10, 11 | Monthly |
| Ammoniacal Nitrogen | Monthly* | Mean**: 25 mg/L 95 th percentile**: 30 mg/L | 10, 11 | Monthly |
| Total Phosphorus | Monthly* | Mean**: 8 mg/L 95 th percentile**: 10 mg/L | 10, 11 | Monthly |
| BOD ₅ | Monthly* | N/A | 10 | Monthly |
| Total Suspended Solids | Monthly* | N/A | 10 | Monthly |
| <i>Escherichia coli</i> | Monthly* | 95 th percentile**: 250,000 cfu/100 mL | 10, 11 | Monthly |
| Nitrogen Loading | Annual | 1,223 kg/ha/year | 7, 12 | Annual |

*Last week of each month ** Calculated on a 12 Month Rolling Mean or 95th percentile

All sampling is carried out by Watercare to the required Standards specified in Condition 11 (Watercare Laboratory Services is IANZ accredited to NZS/ISO/IEC 17025).



4 WASTEWATER FLOWS AND SAMPLING

4.1 Wastewater Flows

The daily wastewater flow rates (m³/day) from the oxidation pond are tabulated in Table 4.1 and graphically represented in Figure 4.1. The total wastewater flow for the year is 92,333 m³, up 5,929 m³ (or nearly 7%) from the previous period of 86,404 m³ and up 17,863 m³ (24% increase) from 74,470 m³ during the 2016-2017 period.

The wastewater discharge flow rate has a consented maximum volume of 775 cubic metres per day. Discharge volumes greater than this were recorded on 01/06/19, 07/06/19, 23/08/19 and 24/08/19. The elevated volumes recorded in June were due to the ponds reaching critical level and the discharge valve needing to be operated manually. Leading up to these dates, blockages in the discharge pipes resulted in lower discharge volumes than usual, with the pond then reaching critical level. The discharge valve was operated manually on the two dates to reduce the level and protect the integrity of the pond. The elevated volumes recorded in August were due to a high-level alarm and the valve on the pipe to the trench not being closed fully after being opened manually.

The annual average was 253 m³/day for the 2018-2019 monitoring period.




Figure 4.1: Wastewater Flows from Outlet Pipe 2018-2019



Table 4.1: Wastewater Flows 2018-2019

| Date | Hawea WWTP Trench Discharge Flow (m ³) | Hawea WWTP Irrigation LTA (m ³) | Irrigation (mm) * | Hawea Outlet Flow Total (m ³) |
|--------------|--|---|-------------------|---|
| December | 101 | 7,752 | 332.7 | 7,853 |
| January | 299 | 6,641 | 285.0 | 6,940 |
| February | 483 | 6,785 | 291.2 | 7,268 |
| March | 669 | 5,432 | 233.1 | 6,101 |
| April | 354 | 8,841 | 379.4 | 9,195 |
| May | 6,206 | 1,821 | 78.2 | 8,027 |
| June | 9,890 | 0 | 0.0 | 9,890 |
| July | 9,075 | 0 | 0.0 | 9,075 |
| August | 8,062 | 0 | 0.0 | 8,062 |
| September | 2,080 | 4,070 | 174.7 | 6,150 |
| October | 771 | 6,029 | 258.8 | 6,800 |
| November | 4,429 | 2,543 | 109.1 | 6,972 |
| Total | 42,419 | 49,914 | 2,142.2 | 92,333 |

* Is the irrigation depth over the 2.33 ha LTA.

The treated wastewater has been evenly split between the disposal trench and the spray irrigation system. The number of days (>10 m³) discharging to spray irrigation has been 176 and to the disposal trench was 186 (note that both the trench and irrigation can be used the same day with a total daily discharge limit of 775 m³). This is compared to the 2017-2018 period when the spray irrigation was only used for 115 days and the disposal trench was used 268 days.

However, the activity is still non-compliant as the disposal trench has been used for more than four months in the calendar year. QLDC are aware of this issue and are working with the contractors (Veolia) to remedy this. Veolia have commented that they are limiting the use of spray irrigation when the wind is => 10 km/hour or if rainfall is >15 mm/day. The 10 km/hr limit is lower than what is required by the consent at 29.9 km/hr. QLDC are working with Veolia to determine if spray drift is occurring at winds over 10 km/hr or if it should be used up to 29.9 km/hr consent limit and therefore require less discharge to disposal trench.

4.2 Wastewater Sampling

Treated wastewater from the outlet of the pond is sampled on a monthly basis. A representative sample is collected and analysed for a total of six parameters (total ammoniacal nitrogen, total phosphorus, total nitrogen, total suspended solids, BOD₅ and *E. coli*) as per Resource Consent RM10.308.02. Those parameters that have consent limits in Resource Consent RM10.308.02 are presented in tabular (refer to Table 4.2) and graphical (Figure 4.2 and Figure 4.7) format.



Table 4.2: Summary of Wastewater Monitoring Results for 2018-2019

| Parameter | Consent Limit (calculated on a 12-month rolling period) | Rolling 95 th Percentile mg/L | Annual Mean mg/L | Max mg/L | Min mg/L |
|------------------------|--|--|------------------|----------|----------|
| BOD ₅ | - | - | 29 | 48 | 8.1 |
| Total Suspended Solids | - | - | 99 | 280 | 35 |
| Total Nitrogen | Mean: 35 mg/L 95 th percentile: 40 mg/L | 89 | 55 | 110 | 22 |
| Total Phosphorus | Mean: 8 mg/L 95 th percentile: 10 mg/L | 10 | 8 | 11 | 6.1 |
| Ammoniacal Nitrogen | Mean: 25 mg/L 95 th percentile: 30 mg/L | 46 | 35 | 50 | 4 |
| <i>E. coli</i> | 95 th percentile: 250,000 cfu/100 mL | 168,500 | 57,308 | 240,000 | 3,000 |

The rolling 12 month 95th percentile for *E. coli* remained well within the consent limit of 250,000 CFU/100 ml during the 2018-2019 monitoring period (refer to Figure 4.2). The maximum concentration of *E. coli* over the year was 240,000 cfu/100 mL with a count reduction to 20,000 cfu/100 mL the following month. The annual mean of 57,308 cfu/100 mL was noted to be higher than the 2017-2018 count of 38,175 cfu/100 mL.




Figure 4.2: *E. coli* in Wastewater

The rolling 12 month 95th percentile of 46 mg/L and the annual mean of 35 mg/L for total ammoniacal nitrogen exceeded the consent limit (30 mg/L and 25 mg/L respectively) in the 2018-2019 monitoring period (refer to Figure 4.3). The 95th percentile has exceeded the consented limit since 2011-2012 monitoring period (8 calendar years). The annual mean was 11 mg/L higher



than the 2017-2018 monitoring period. Measures to address this have been outlined in the sections below.




Figure 4.3: Ammoniacal Nitrogen in Wastewater

The rolling 12 month 95th percentile of 89 mg/L and the annual mean of 55 mg/L for total nitrogen exceeded the consent limit (40 mg/L and 35 mg/L respectively) in the 2018-2019 monitoring period (refer to Figure 4.4). The maximum concentration of total nitrogen over the year was 110 mg/L. The annual 95th percentile and annual mean have also been exceeded the consent limits in 2015-2016, 2016-2017 and 2017-2018. Measures to address this have been outlined in the sections below.




Figure 4.4: Total Nitrogen in Wastewater

Total suspended solids, total phosphorus and BOD₅ are consistent with the results in previous years (refer to Figure 4.5 to Figure 4.7). Total phosphorus remained compliant with the rolling 95th percentile and the annual mean. There are no consent limits for total suspended solids and BOD₅.




Figure 4.5: Total Phosphorus in Wastewater




Figure 4.6: Total Suspended Solids in Wastewater




Figure 4.7: BOD₅ in Wastewater



5 NITROGEN MASS BALANCE

Treated wastewater is evenly applied by spray irrigation over 2.33 hectares area planted with ryegrass. The land management regime is cut and carry with no stock grazing.

Condition 12 of Resource Consent RM10.308.02 requires that a nitrogen mass balance for the spray irrigation land application area is prepared annually. This is to include the following:

- *The nitrogen mass balance shall consist as a minimum the total nitrogen applied to land and crop removal of nitrogen.*
- *The total nitrogen applied to the spray irrigation land shall be estimated from the total volume of wastewater applied and the average monthly concentration of total nitrogen in the land applied wastewater.*
- *The crop removal of nitrogen from the spray irrigation land shall be estimated by obtaining dry matter content and total nitrogen content after each crop/plant harvest.*
- *The nitrogen mass balance from condition 12(a) and any other factors such as ammonia volatilisation and denitrification shall be used to calculate the mass of nitrogen leached from the site, using a model acceptable to the consent authority.*

5.1 Mean Wastewater Nitrogen Concentration

The influent loads, operation and performance of the oxidation pond affect the concentration of Total Nitrogen (TN) in the effluent. The input into the nitrogen balance model is based on the average (mean) of the water quality analysis results sampled from the outlet of the oxidation pond prior to application to land for the period under consideration. The values used in the model (Appendix E) are the concentrations measured each month at the outlet of the oxidation pond during the 12-month data analysis period (Appendix B). Quantities of nitrogen applied by spray irrigation to the LTA and discharged to the trench are presented in Table 5.1 below.

Table 5.1: Nitrogen Discharged to Trench and Applied on LTA between December 2018 - November 2019

| Date | Nitrogen Concentration at Outlet (mg/L) | Monthly Nitrogen Applied by Spray Irrigation (kg/ha) | Total Nitrogen Applied by Spray Irrigation (kg) | Total Nitrogen Discharged to Trench (kg) |
|--------------|---|--|---|--|
| December | 55.0 | 183.0 | 426.4 | 5.6 |
| January | 65.0 | 185.3 | 431.7 | 19.4 |
| February | 56.0 | 163.1 | 380.0 | 27.0 |
| March | 52.0 | 121.2 | 282.5 | 34.8 |
| April | 22.0 | 83.5 | 194.5 | 7.8 |
| May | 27.0 | 21.1 | 49.2 | 167.6 |
| June | 39.0 | 0.0 | 0.0 | 385.7 |
| July | 46.0 | 1.2 | 2.7 | 417.5 |
| August | 55.0 | 0.0 | 0.0 | 443.4 |
| September | 110.0 | 192.1 | 447.7 | 228.8 |
| October | 62.0 | 160.4 | 373.8 | 47.8 |
| November | 71.0 | 77.5 | 180.6 | 315.5 |
| Total | 55.0 (mean) | 1,188 | 2,769 | 2,100 |



Monthly wastewater samples for the reporting period show significant variation in the percentage of Ammoniacal Nitrogen/Total Nitrogen with values ranging from less than 17% (April) to 83% (July). Table 5.2 compares the mean percentage of Ammoniacal Nitrogen/Total Nitrogen over the last three reporting periods. The 2018-2019 reporting period was 63% up slightly at 55% from the 2017-2018 period and the 2016-2017 period. Although ammonia is toxic to aquatic life at certain pH and temperatures, it is not important to remove it for discharges to land and it is actually more beneficial from a nitrogen leaching perspective as ammonia is less mobile in the soil than nitrate.

The percentage of Ammoniacal Nitrogen in the pond system with a theoretical retention time of 50 days, remains high compared to typical municipal treated wastewater values and is likely a result of the temperature being too cold for nitrification to occur in the winter months. However, it could also be a lack of alkalinity as suggested in the ERPRO Report from the 20th September 2019 and earlier LEI Nitrogen Balance Reports.

Table 5.2: Comparison of the Percentage of Ammoniacal Nitrogen in Total Nitrogen Between 2015 and 2019

| | 2016-2017 | 2017-2018 | 2018-2019 |
|------------------------|------------------|------------------|------------------|
| December | 73.5% | 75.0% | 69.1% |
| January | 6.4% | 34.1% | 66.2% |
| February | 5.3% | 0.6% | 75.0% |
| March | 18.9% | 3.5% | 73.1% |
| April | 69.6% | 7.6% | 17.3% |
| May | 71.4% | 59.3% | 48.1% |
| June | 87.8% | 88.2% | 76.9% |
| July | 56.5% | 84.4% | 82.6% |
| August | 79.5% | 83.7% | 70.9% |
| September | 75.0% | 69.2% | 39.1% |
| October | 83.3% | 74.1% | 67.7% |
| November | 1.4% | 75.4% | 70.4% |
| Mean Percentage | 52.4% | 54.6% | 63.0% |

5.2 Nitrogen Losses

Nitrogen loss to the ground is based on a Loss Factor (LF) and exported nitrogen. LF takes three parameters into consideration: denitrification, soil storage and ammonia volatilisation.

The ammonia volatilisation percentage of 15% for spray irrigation has been used. This is seen as the mid-range of what would be expected.

Denitrification has been taken as 10% of the applied nitrogen. This is based on the Peer Reviewed Jacks Point model and is considered conservative as the whole soil profile is available here for denitrification and irrigation only occurs in the warmer months, whereas at Jacks Point, the effluent was discharged 200 mm below ground and was also applied all year round.

The total Loss Factor is calculated to be 19.5% in the model which represents an increase of 1.3% compared to the previous period from 18.2%.

5.3 LTA Nitrogen Loading (kg/ha)

This is determined based on the combination of effluent flow, nitrogen concentration in the effluent, effluent irrigated and LTA area.



5.4 Pasture Nitrogen Uptake and Cut & Carry Removal

The amount of nitrogen uptake and the cut & carry removal is calculated as a proportion of the dry matter production, based on a percentage of utilisation. The new sowed ryegrass is cut, baled and weighed. The Dry Matter (DM) nitrogen content is then calculated and entered in the Nitrogen Mass Balance.

Three cuts were taken offsite during the reporting period: February 2019, May 2019 and November 2019 and are shown in Table 5.3.

Table 5.3: Nitrogen Removed by Cut and Carry

| Date of Cut | Ryegrass Harvested (kg) | % Dry Matter | Nitrogen Concentration (%) | Nitrogen Removed with the Crop (kg N) | Nitrogen Removed per Hectare (kg N/ha) |
|--------------|-------------------------|--------------|----------------------------|---------------------------------------|--|
| Feb-19 | 22,750 | 40% | 2.3% | 209.3 | 89.8 |
| 2-May-19 | 11,700* | 63% | 1.6% | 121.1 | 52.0 |
| 4-Nov-19 | 32,500 | 24% | 3.0% | 235.1 | 100.9 |
| Total | 66,950 | | | 565.5 | 243 |

* No data was given on the weight and number of bales exported

5.5 Leached Nitrogen (kg/ha) from Spray Irrigation Area

The overall nitrogen balance for the site is shown in Table 5.4. Other factors have been modelled, such as ammonia volatilisation, denitrification and soil storage. The negative leaching loss from the mass balance reflects the close match between nitrogen added and nitrogen exported in the baleage.

Table 5.4: Overall Nitrogen Balance for LTA

| Year | Nitrogen Applied (kg N/ha/yr) | Nitrogen Losses (kg N/ha/yr) | Nitrogen Exported in Plants (kg N/ha/yr) | Nitrogen Leached (kg N/ha/yr) |
|-----------|-------------------------------|------------------------------|--|-------------------------------|
| 2015-2016 | 229 | 42 | 194 | 0 (-7) |
| 2016-2017 | 223 | 40 | 79 | 104 |
| 2017-2018 | 358 | 65 | 158 | 134 |
| 2018-2019 | 1,188 | 231 | 243 | 714 |

The nitrogen loading rate to the LTA has significantly increased from previous years due to the increase in flow to the site (up 7% from 2017-2018 and 24% from 2016-2017) and increase in the concentration of nitrogen in the wastewater (up 41% from 2017-2018 and 48% from 2016-2017).

5.6 Overall Annual Nitrogen Mass Balance for the Hawea WWTP

The annual nitrogen mass balance for the Hawea LTA is calculated by multiplying the per hectare results ('N loading', 'Cut and Carry removal', and 'Nitrogen losses') by the area of the LTA (2.33 ha). This gives the 'Total N leached' in units of kg N/yr. The results of the annual nitrogen balance are shown in Table 5.5. Three cuts were taken offsite during the reporting period, in February 2019, May 2019 and November 2019.



Table 5.5: Nitrogen Balance (kg N/yr)

| Year | Land use | Nitrogen Applied (kg N/yr) | Nitrogen Losses (kg N/yr) | Nitrogen Exported in Plants (kg N/yr) | Nitrogen Leached (kg N/yr) |
|------------------|--------------|----------------------------|---------------------------|---------------------------------------|----------------------------|
| 2016-2017 | LTA | 519 | 93 | 184 | 245 |
| | Trench | 1,652 | 0 | 0 | 1,652 |
| | Total | 2,171 | 93 | 184 | 1,857 |
| 2017-2018 | LTA | 834 | 152 | 369 | 313 |
| | Trench | 2,580 | 0 | 0 | 2,580 |
| | Total | 3,414 | 152 | 369 | 2,893 |
| 2018-2019 | LTA | 2,769 | 538 | 566 | 1,924 |
| | Trench | 2,100 | 0 | 0 | 2,100 |
| | Total | 4,869 | 538 | 566 | 3,765 |

Nitrogen leaching has increased by 30% to 3,765 kg N/yr from the 2017-2018 reporting period (2,893 kg N/yr) and 102% from the 2016-2017 reporting period (1,857 kg N/yr).

The improvement in the operation of the spray irrigation has resulted in a 103% increase in the removal of nitrogen (nitrogen exported and gaseous losses) to 1,104 kg from 521 kg in 2017-2018, that would have otherwise leached through the trench.

During the 2018-2019 reporting period, three cuts of baleage were with an estimated 566 kg N removed from the LTA through the cut and carry of the ryegrass which has increased by 53% from 2017-2018 (360 kg N) and 207% from 2016-2017 (184 kg N).

However, it wasn't enough to balance the increase flow into the plant as well as the increased concentration of nitrogen in the wastewater.



6 RESOURCE CONSENT REQUIREMENTS AND COMPLIANCE

6.1 Consent Compliance for 1 December 2018 to 30th November 2019

Compliance with Resource Consents RM10.308.01 and RM10.308.02 is displayed in Table 6.1 and Table 6.2 by condition.

Veolia is the 3-waters (water, wastewater and stormwater) operators and maintenance contractor for QLDC. In the 1 December 2018 to 30 November 2019 period there were only minor system faults that occurred and were rectified, but no major breakdowns, as shown in Appendix F. Veolia manages programmed maintenance and work orders/ requests for service for breakdowns.

As detailed in Section 4.1 of the report, elevated volumes were recorded in June were due to the ponds reaching critical level and the discharge valve needing to be operated manually. Leading up to these dates, blockages in the discharge pipes resulted in lower discharge volumes than usual, with the pond then reaching critical level. The discharge valve was operated manually on the two dates to reduce the level and protect the integrity of the pond.

There have been some improvements to the use of spray irrigation over the disposal trench when compared to previous years. Over the winter months when spray irrigation can't be used during to freezing conditions, previously it was November in 2018 and October 2017 before they would start using spray irrigation, but this year spray irrigation was started up again in mid-September. However, the disposal trench is still being used too frequently outside of these winter months. QLDC are aware of this issue and are working with the contractors (Veolia) to remedy this. Veolia have commented that they are limiting the use of spray irrigation when the wind is \geq 10 km/hour or if rainfall is $>$ 15 mm/day. The 10 km/hour limit is lower than what is required by the consent at 29.9 km/hour. QLDC are working with Veolia to determine if spray drift is occurring at winds over 10 km/hour or if it should be used up to 29.9 km/hour consent limit and less discharge to disposal trench.

As stated in previous reports, it has been determined that the plant is not suitable for the current resource consent conditions. There is no design basis for the oxidation pond to remove nutrients reliably. This calendar year QLDC engaged ERPRO to review the operation of the pond and make recommendations in regard to how the plant could be brought back into compliance. The report is attached as Appendix H for reference. Subsequently QLDC have been assessing the practicalities of implementing the options proposed. They have discounted the option to dose with lime due to difficulties with configuring mixing system, and also the external biotreatment option as a result of the associated costs. As such the preferred option is to dose the ponds with Zeolite to reduce Ammonia levels. QLDC are currently establishing the method to dose the product into the pond and their target completion date is the end of January 2020. This will be a short-term solution to improve nitrogen levels, until the wastewater can be diverted to the Wanaka WWTP around May 2022.

In the meantime, QLDC are also sampling the Hawea River upstream and downstream to determine what the potential effects are of the high Total Nitrogen and Ammoniacal Nitrogen discharge into the downstream environment. They will continue to monitor once the Zeolite has been added into the ponds in January 2020.



Table 6.1: Discharge to Air Permit RM.10.308.01 Conditions

| Condition | Clause Condition | Comments | Compliance |
|------------------|--|--|-------------------|
| 1 | This consent shall only be exercised in conjunction with Discharge Permit RM10.308.02. | | Achieved |
| 2 | The discharge to air shall be as described in the consent application submitted to the Consent Authority on 31 August 2010 and any subsequent information provided. | | Achieved |
| 3 | Wind cloth shall be installed on the western, southern and eastern-most boundaries of the area on which treated wastewater is to be applied by spray irrigation. This wind cloth shall be maintained until the screen foliage required under condition 4 is fully established. | The wind cloth was installed prior to 1 December 2012 and is still in place. | Achieved |
| 4 | Suitable screening foliage, that shall be at least 3 metres high but not exceed 6 metres in height, shall be planted on the western, southern and eastern-most boundaries of the area on which treated wastewater is applied by spray irrigation. | to the screen foliage was planted prior 1 December 2012 and is currently 3 metres in height. | Achieved |
| 5 | A weather station shall be installed in an appropriate location to record, as a minimum, rainfall and wind conditions at the site where treated wastewater is to be applied by spray irrigation. | The weather station was installed in August 2011 and is in good working order. | Achieved |
| 6 | The spray irrigation system shall not be operated in conditions where wind speed, as measured at the on-site station installed under condition 5, exceeds 29.9 km/hour. | Control system installed to meet this condition. | Achieved |
| 7 | The consent holder shall keep a record of any complaints received regarding discharges of odour from the site. The record shall, as a minimum, include the following: (a) the time and place at which the complaint was generated; (b) the nature of the complaint; (c) operating conditions at the time of the complaint, including any malfunctioning or breakdown of control equipment; (d) wind and weather conditions at the time of the complaint; and (e) corrective action taken by the consent holder to minimise the risk and extent of the recurrence of the causes of the complaint. The consent holder shall submit a copy of the written record of the complaint to the consent authority within two weeks after any complaint occurring, together with the details of the corrective actions taken. | No odour complaints recorded for the 2018-2019 year. | Achieved |
| 8 | There shall be no discharge of odour, as a result of the exercise of this consent, that is noxious, dangerous, offensive or objectionable to the extent that it causes an adverse effect beyond the boundary of the site, in the opinion of an authorised officer of the Consent Authority. | No odour complaints recorded for the 2018-2019 year. | Achieved |



Table 6.2: Discharge to Land Permit RM10.308.02 Conditions

| Condition | Clause Condition | Comments | Compliance |
|------------------|--|--|----------------------|
| 1 | The discharge shall only be treated wastewater, as described in the consent application submitted to the Consent Authority on 31 August 2010 and any subsequent information provided. | | Achieved |
| 2 | The volume of effluent discharged shall not exceed 775 cubic metres per day. | Refer to Appendix D. Generally compliant, with two days in June 2019 and two days in August 2019 recorded at elevated volumes. | Non-compliant |
| 3 | The distance the site boundary from any part of the wastewater treatment and disposal system shall no less than 5 metres. | Compliant. | Achieved |
| 4 | By no later than 1 December 2012, the consent holder shall ensure that the trench utilised for wastewater disposal: a) is at least 150 metres long and 2 m wide in total; and b) is intermittently dosed; and c) is not used for the disposal of wastewater for more than 4 months in total in any one calendar year. | The trench has been used for more than 4 months per calendar year. | Non-compliant |
| 5 | By no later than 1 December 2012, the consent holder shall install and commission a spray irrigation system for the land application of treated wastewater. The spray irrigation system shall meet the following criteria: (a) the total area on which treated wastewater is applied by spray irrigation shall be no less than 2.33 hectares; (b) treated wastewater shall be applied evenly by spray irrigation to the area defined in appendix I only; (c) the area on which treated wastewater is applied by spray irrigation shall be fenced with a 2 metre high deer fence with appropriate signage warning the general public of the hazard; (d) a weather station shall be installed in an appropriate location to record, as a minimum, rainfall and wind conditions at the site where treated wastewater is to be applied by spray irrigation; (e) wastewater shall not be applied to land by spray irrigation system during the hours outside of 11 pm to 5 am; (f) nozzle pressure must not exceed 400 kilopascals (kPa); (g) there shall be no irrigation of treated wastewater using k-line irrigation systems. | The spray irrigation continues to operate within these criteria. (a) and (b) Spray irrigation is applied to 2.33 hectares in the area shown on the plan; (c) The deer fencing is in place and still intact; (d) The weather station is in good working order; it records as a minimum rainfall and windspeed; (e) Wastewater is not applied during these hours; (f) The nozzle pressure is alarmed so that it does not exceed 400 kPa; (g) There is no k-line used for irrigating. | Achieved |



| Condition | Clause Condition | Comments | Compliance |
|-----------|--|---|-----------------|
| 6 | The area on which treated wastewater is to be applied using spray irrigation shall be planted in high growth and nitrogen uptake vegetation (such as lucerne or ryegrass) and shall be managed as far as practicably possible to optimise nutrient removal. A minimum of three harvests per year shall be undertaken. | Harvests were undertaken in February, May and November 2019. | Achieved |
| 7 | The total nitrogen applied to the spray irrigation area shall not exceed 1,223 kilograms of nitrogen per hectare per year. | The total nitrogen applied to the spray irrigation area was 1,188 kg/ha for the 2018-2019 year. The nitrogen mass balance is provided in Section 5. | Achieved |
| 8 | The treatment and disposal system shall be constructed and installed in accordance with the details and plans supplied with the consent application submitted to the consent authority on 31 August 2010, and attached to this consent as appendix I. | Spray irrigation system installed 5 December 2012. | Achieved |
| 9 | The consent holder shall install a flow meter on the outlet pipe from the treatment system and continually measure and record the daily volume (based on a no more than weekly average) of effluent being discharged to the disposal field. The consent holder shall forward the record for the previous 12-month period to the consent authority by 1 December each year, and upon request. | The recorded daily volume is provided in Appendix D. | Achieved |



| Condition | Clause Condition | Comments | Compliance | | | | | | | | | | | | | | | |
|-------------------------|---|--|-----------------|--------------------------------------|---------------------|-----------|-----------|----------------|-----------|-----------|-------------------|----------|-----------|-------------------------|---|----------------------------------|--|----------------------|
| 10 | <p>(a) from the first exercise of this consent, the consent holder shall collect representative samples of the treated wastewater from the outlet of the oxidation pond in the last week of each month. The samples shall be analysed for: (i) Five-day total biochemical oxygen demand (BOD₅); and (ii) Total Suspended Solids; and (iii) Total Nitrogen; and (iv) Total Ammoniacal Nitrogen; and (v) Total Phosphorous; and (vi) <i>Escherichia coli</i></p> <p>(b) from the first exercise of this consent, wastewater discharged from the oxidation pond shall comply with the following criteria:</p> <table border="1" data-bbox="344 480 1128 675"> <thead> <tr> <th></th> <th>Mean*</th> <th>95th percentile (mg/l) *</th> </tr> </thead> <tbody> <tr> <td>Ammoniacal nitrogen</td> <td>25 (mg/l)</td> <td>30 (mg/l)</td> </tr> <tr> <td>Total nitrogen</td> <td>35 (mg/l)</td> <td>40 (mg/l)</td> </tr> <tr> <td>Total phosphorous</td> <td>8 (mg/l)</td> <td>10 (mg/l)</td> </tr> <tr> <td><i>Escherichia coli</i></td> <td>-</td> <td>2.5 x 10⁵ cfu/100 ml</td> </tr> </tbody> </table> <p><i>*the mean and 95th percentile apply to a rolling 12-month period.</i></p> <p>(c) the analytical sample results from the sampling under condition 9(a) of this consent shall be submitted to the consent authority by 1 December each year and upon request.</p> | | Mean* | 95 th percentile (mg/l) * | Ammoniacal nitrogen | 25 (mg/l) | 30 (mg/l) | Total nitrogen | 35 (mg/l) | 40 (mg/l) | Total phosphorous | 8 (mg/l) | 10 (mg/l) | <i>Escherichia coli</i> | - | 2.5 x 10 ⁵ cfu/100 ml | <p>Samples have been collected every month.</p> <p>Section 4 above summarises the results for each of the determinants. Refer to Appendices B and C for full results.</p> <p>Elevated results have been recorded for the annual mean and 95th percentile for both total nitrogen and ammoniacal nitrogen.</p> | Non-compliant |
| | Mean* | 95 th percentile (mg/l) * | | | | | | | | | | | | | | | | |
| Ammoniacal nitrogen | 25 (mg/l) | 30 (mg/l) | | | | | | | | | | | | | | | | |
| Total nitrogen | 35 (mg/l) | 40 (mg/l) | | | | | | | | | | | | | | | | |
| Total phosphorous | 8 (mg/l) | 10 (mg/l) | | | | | | | | | | | | | | | | |
| <i>Escherichia coli</i> | - | 2.5 x 10 ⁵ cfu/100 ml | | | | | | | | | | | | | | | | |
| 11 | <p>All sampling techniques shall be acceptable to the consent authority. All analysis carried out in connection with this consent shall be performed by a laboratory that meets ISO 17025 standards, or otherwise as specifically approved by the consent authority.</p> | <p>Sampling and lab analysis performed monthly by Watercare Laboratories to meet the required standards.</p> | Achieved | | | | | | | | | | | | | | | |



| Condition | Clause Condition | Comments | Compliance |
|-----------|--|--|------------------------|
| 12 | <p>The following information shall be provided in writing to the consent authority by 1 December each year, and upon request, following the commencement of the exercise of the consent:</p> <p>(a) The nitrogen mass balance for the spray irrigation land application area, which shall be determined annually. The nitrogen mass balance shall consist as a minimum the total nitrogen applied to land and crop removal of nitrogen.</p> <p>(b) The total nitrogen applied to the spray irrigation land shall be estimated from the total volume of effluent applied and the average of monthly concentration of total nitrogen in the land applied effluent.</p> <p>(c) The crop removal of nitrogen from the spray irrigation land shall be estimated by obtaining dry matter content and total nitrogen content after each crop/plant harvest.</p> <p>(d) The nitrogen mass balance from condition 12(a) and any other factors such as ammonia volatilisation and denitrification shall be used to calculate the mass of nitrogen leached from the site, using a model acceptable to the consent authority</p> | <p>The nitrogen mass balance is presented in Section 5 and covers requirements outlined in the consent condition.</p> | <p>Achieved</p> |
| 13 | <p>The consent holder shall forward an annual report in writing to the consent authority by 1 December each year. The annual report shall cover the preceding 12-month period (from 1 December the preceding year until 30 November of the current year) and shall report on compliance with this consent. As a minimum, the report shall include:</p> <p>(a) A summary of all analytical results for the year; and</p> <p>(b) A summary of the year's monitoring results, in context of previous years' results; and</p> <p>(c) Comments on compliance with the conditions of this discharge permit; and (d) A summary of any complaints received, the validity of each complaint and the corrective action taken; and</p> <p>(e) A summary of any malfunctions of breakdowns and the corrective action taken; and</p> <p>(f) Details of the cut and carry operation, including the calculations for nitrogen loading in the spray irrigation land, number of harvests, dry matter and total nitrogen content of the harvest and nitrogen balance for this site.</p> <p>(g) Any other issues considered relevant by the consent holder.</p> | <p>Annual Report submitted for the period 1 December 2018 – 30 November 2019 in December 2019.</p> <p>Please note that the wording of this condition requires an annual report to be submitted only one day following the end of the monitoring period. This is impractical because if sampling is undertaken in the last week of the month as required by the condition 10a, the results wouldn't be available for reporting before the end of November. Furthermore, the report incorporates the flow results right up to the end of November.</p> | <p>Achieved</p> |



| Condition | Clause Condition | Comments | Compliance |
|-----------|---|---|------------|
| 14 | <p>By no later than 1 December 2012, the consent holder shall prepare and forward to the consent authority an operations and management manual for the wastewater treatment and disposal system to ensure its effective and efficient operation at all times. The system shall be operated in accordance with this manual, which shall be updated as appropriate. The manual and include, as a minimum:</p> <p>(a) A brief description of the treatment and disposal system, including a site map indicating the location of the treatment and disposal system, points of discharge and any monitoring sites;</p> <p>(b) Key operational matters, including weekly, monthly and annual maintenance checks;</p> <p>(c) Monitoring requirements and procedures including a nitrogen balance sheet for the purpose of managing nitrogen inputs and outputs including nitrogen leaching losses;</p> <p>(d) A management plan for the cut and carry operation including procedures for harvesting grass from the site, and maximising grass growth and nitrogen uptake by grass such as soil tests, supplementary nutrient additions and pest and weed control;</p> <p>(e) Management and dosing of trenches</p> <p>(f) Contingency plans in the event of system malfunctions or breakdowns; and (g) The means of receiving and dealing with any complaints; and</p> <p>(h) Emergency contact phone numbers.</p> | <p>The first Operation and Maintenance manual was sent to the ORC on the 7 May 2008, with revisions/updates on the 8th August 2008, April 2010, and 6th December 2017. There have been no further updates to the O&M.</p> <p>Maintenance has been undertaken in accordance with the O&M on a weekly, monthly and yearly basis.</p> | Achieved |
| 15 | No ponding or surface run-off of effluent shall occur as a result of the exercise of this consent. | No ponding or surface run-off of wastewater. | Achieved |
| 16 | There shall be no odour emission resulting from the treatment and disposal system that is offensive or objectionable to such an extent that it has an adverse effect on the environment beyond the boundary of the property on which the consent is exercised. | No odour complaints received within the 2018-2019 year. | Achieved |
| 17 | This permit does not authorise the discharge of sludge to land or water. | No sludge discharged to land or water. | Achieved |



6.2 Previous Consent Compliance

On the 30 January 2019 Environmental Officer, Stephen Smith from the Otago Regional Council undertook a compliance monitoring audit. The results of that audit were provided to QLDC in a report dated 10 June 2019. The report identifies a number of non-compliances which are considered to have significant actual or potential environmental effects.

The non-compliances are for the reporting period of 1 December 2017 to 30th November 2018 and relate to the volume of flow discharged exceeding the limit of 775 m³ on four occasions, operating the disposal trench for more than 4 months in any one calendar year, only undertaking two harvests of Lucerne and samples of wastewater not meeting consent trigger levels. The report recommended that QLDC prepare a transition proposal to compliance that was suitable to the Manager of Compliance (Martin King).

A formal warning letter was issued on the 17th June 2019 specifically requesting that QLDC undertake the following actions:

1. Undertake regular concurrent sampling of the Hawea River both upstream and immediately downstream of the treatment plan to test for the presence and concentration of ammoniacal nitrogen, total nitrogen and *E. coli* and report the results of this sampling to ORC;
2. Notify ORC immediately if the downstream sample results show greater results than is present in the upstream samples;
3. Implement procedures and systems to ensure the correct operation and management of the spray and trench application systems so that they can comply with the consent conditions;
4. Confirm the date for decommissioning of the plant;
5. Consider and implement as necessary the recommendations specified in the reports from LEI 2014, 2016 and 2018 to ensure compliance with consent conditions.

6.3 Progress Towards Compliance

On 26 July 2019 in a letter to ORC, QLDC acknowledged the seriousness of the non-compliances and prepared a transition proposal to compliance outlining their response to the above actions:

1. QLDC have engaged WaterCare Laboratory Services to take samples of the Hawea River upstream 85 metres upstream of the edge of the disposal trench and 145 metres downstream of the southern edge of the spray irrigation field. Sampling commenced on the 20th May 2019 and are collected on a monthly basis to coincide with wastewater sampling and have been analysed for Ammoniacal Nitrogen (NH₃-N), Biochemical Oxygen Demand (BOD), Dissolved Reactive Phosphorus (DRP), pH, Total Nitrogen (TN), Total Oxidised Nitrogen (TON), Total Phosphorus (TP), Total Suspended Solids (TSS) and *Escherichia coli* (*E. coli*). The results are provided in Appendix G and show that downstream samples in:
 - a. June 2019 for TN, DRP and *E. coli* were higher than upstream;
 - b. July and August 2019 for TN was only slightly higher than the upstream sample; and
 - c. October 2019 for NH₃-N, TN and *E. coli* were higher than the upstream sample;
 - d. November 2019 were the same as recorded upstream.
2. QLDC agrees to notify the ORC immediately in the event that the downstream results exceed the upstream results. The results have also been compared against relevant values in the Regional Plan Water and guidelines. QLDC seek to get agreement from ORC regarding suitable guideline values to compare the downstream samples against in the



- event of an exceedance to apply context. Furthermore, QLDC will investigate the potential causes of the elevated results and provide a written explanation to ORC within 7 days.
- a. The June, July, August and October river sampling results have been provided alongside the routine wastewater monitoring results monthly to ORC. The results were not provided immediately to ORC as the downstream results were still relatively low when compared to guideline values and there is only a small variation between upstream and downstream.
 - b. ORC have provided a verbal confirmation that they accept the proposed guideline value, but as ORC have written a formal warning letter; QLDC require that these GV's are confirmed in writing so an agreement can be reached regarding notification.
3. The following actions to improve the management of the LTA and disposal trenches:
- a. QLDC turned the irrigation system on in September 2019 (compared with November in 2018 and October in 2017). QLDC have queried Veolia as to the disposal trench has been used regularly since the irrigator was turned on. Veolia have commented that they are limiting the use of spray irrigation when the wind is \geq 10km/hour or if rainfall is $>$ 15 mm/day. The 10 km/hour limit is lower than what is required by the consent at 29.9 km/hour. QLDC are working with Veolia to determine if spray drift is occurring at winds over 10 km/hour or if it should be used up to 29.9 km/hour consent limit and less discharge to disposal trench.
 - b. The LTA was re-sown with ryegrass in October 2018 and the weed managed so that three harvests (January, May and November) were completed for the 2018-2019 reporting period.
 - c. Daily discharge volume alarm was installed in October 2018 that notifies the contractor when volumes exceed 600 cubic metres.
 - d. An alarm has also been installed to manage the pond below critical level this was completed in August 2019.
4. There are two capital works programmes planned (pump station and pipeline from Hawea to Project Pure, and upgrade of the Project Pure plant to provide treatment capacity) and target completion date is May 2022.
5. The four recommendations from the LEI reports are:
- a. Operation of the LTA and disposal trench – ongoing as discussed above;
 - b. Low ammonia removal efficiency – QLDC engaged with ERPRO to review the operation of the pond and make recommendations in regard to how the plant could be brought back into compliance. The report is attached as Appendix H for reference. Subsequently QLDC have been assessing the practicalities of implementing the options proposed. They have discounted the option to dose with lime due to difficulties with configuring mixing system, and also the external biotreatment option as a result of the associated costs. As such the preferred option is to dose the ponds with Zeolite to reduce Ammonia levels. QLDC are currently establishing the method to dose the product into the pond and their target completion date is the end of January 2020.
 - c. Operation of cut and carry – has been addressed and is discussed above;
 - d. Review of operational flow rate and volume discharge to disposal trench – ongoing as discussed above.
6. Other actions proposed or completed:
- a. Unacceptable weed growth throughout LTA and disposal trench – broom clearance has been undertaken in the vicinity of the disposal trench shown in Figure 6.1, weed control in the LTA is ongoing.
 - b. Remove disconnected overflow pipe – QLDC are still committed to removing the disconnected overflow pipe to provide confidence to the public – Veolia will remove the pipe before the end of December 2019.



- c. Undertake a performance review of the plant and communicate the findings of this with ORC – this has commenced and is discussed under 5b above.



Figure 6.1: Broom Clearance at the at the Disposal Trench

6.4 Further Works to Transition to Compliance

QLDC is committed to implementing a long-term solution, and the QLDC Long Term Plan includes budget for this in 2021 – 2023. A business case for this project has now been approved, demonstrating that conveying the wastewater from Hawea to the Wanaka WWTP is financially and environmentally beneficial. Detailed design on this project is scheduled to commence in 2019.

In the meantime, QLDC are committed to implementing the transition to compliance plan as outlined above with three key areas of focus being:

1. Increasing the operational time of the LTA so that the disposal trench is only used as the default during periods such as ice or snow lie, extreme wet weather, high winds and harvesting;
2. Continue to harvest the crop at least three times every year; and
3. Improving the efficiency of nitrogen and ammonia removal by adding Zeolite;
4. Continue monitoring the water quality in the Hawea River upstream and downstream against relevant guidelines.



7 SUMMARY AND CONCLUSIONS

The interpretation of and conclusion about, the monitoring results for 1st December 2018 to 30th November 2019 reporting period from the Hawea WWTP and consent compliance are as below.

The total wastewater flow for the year is 92,333 m³, up 5,929 m³ (or nearly 7%) from the 2017-2018 period of 86,404 m³ and up 17,863 m³ (24% increase) from 74,470 m³ during the 2016-2017 period.

The annual average was 253 m³/day. The volume of wastewater discharged generally remained below the consent limit of 775 m³/day, with four days recorded in excess of this, on 01/06/19, 07/06/19, 23/08/19 and 24/08/19. The elevated volumes recorded in June were due to a blockage in the outlet pipe in the days leading up to the discharges. This was noticed when a high-level pond alarm was activated and took two discharges to return to normal operating level. The elevated levels in August were due to a high-level alarm and faulty swale valve.

The treated wastewater has been evenly split between the disposal trench and the spray irrigation system. The number of days (>10 m³) discharging to spray irrigation has been 176 and to the disposal trench was 186 (note that both the trench and irrigation can be used the same day with a total daily discharge limit of 775 m³). This is compared to the 2017-2018 period when the spray irrigation was only used for 115 days and the disposal trench was 268 days.

The rolling 12 month 95th percentile of 46 mg/L and annual mean 35 mg/L for total ammoniacal nitrogen exceeded the consent limit (30 mg/L and 25 mg/L) throughout the 2018-2019 monitoring period.

The rolling 12 month 95th percentile of 89 mg/L for total nitrogen exceeded the consent limit (40 mg/L) in the 2018-2019 monitoring period, up 30 mg/L from the 2017-2018 period. The annual mean consent limit was also exceeded.

The results for *E. coli* remained below the consent limit. Total phosphorus, total suspended solids and BOD₅ are consistent with results from previous years. Total phosphorus was compliant with consent limits, while total suspended solids and BOD₅ do not have consent limits.

The nitrogen loading rate has increased from previous years due to the increase in flow to the site (up 7% from 2017-18 and 24% from 2016-2017) and increase in the concentration of nitrogen in the wastewater (up 41% from 2017-2018 and 48% from 2016-2017).

Nitrogen leaching has increased by 30% to 3,765 kg N/yr from the 2017-2018 reporting period (2,893 kg N/yr) and 102% from the 2016-2017 reporting period (1,857 kg N/yr).

The improvement in the operation of the spray irrigation has resulted in a 111% increase in the removal of nitrogen (nitrogen exported and gaseous losses) to 1,104 kg from 521 kg in 2017-2018, that would have otherwise leached through the trench.

During the 2018-2019 reporting period, three cuts of baleage were with an estimated 566 kg of nitrogen removed from the LTA through the cut and carry of the ryegrass which has increased by 54% from 2017-2018 (368 kg) and 207% from 2016-2017 (of 184 kg).

However, it wasn't enough to balance the increase flow into the plant as well as the increased concentration of nitrogen in the wastewater.



Resource Consent RM10.308.01 was compliant with all of its conditions. There were some non-compliant conditions for resource consent RM10.308.02 in the 2018-19. However, there is a plan which includes:

- a. further increasing the operational time of the spray irrigation so that the disposal trench is only used as the default during periods such as ice or snow lie, extreme wet weather, high winds and harvesting;
- b. continuing to review the operation of the crop harvest frequency to see if a fourth harvest could be fit in;
- c. improving the efficiency of nitrogen and ammonia removal by adding Zeolite;
- d. continue monitoring the water quality in the Hawea River upstream and downstream against relevant guidelines; to transition into compliance.

The longer-term solution for Hawea wastewater compliance, is to convey the wastewater to the Wanaka WWTP. This has been budgeted for in 2021-2023, with the detailed design commencing in 2019.



8 REFERENCES

ERPRO (2019) QLDC Lake Hawea WWTP Nitrogen Reduction Implementation.

Otago Regional Council (2019) Hawea Wastewater Treatment Plant. Letter of Formal Warning.

Otago Regional Council (2019) Compliance Monitoring Report. Reference Number A123671.

Otago Regional Council (2010) Discharge Permit RM10.308.01. V1.

Otago Regional Council (2010) Discharge Permit RM10.308.02. V1.

Queenstown Lakes District Council (2018) Hawea Wastewater Treatment Plant Annual Report 2017-2018.



9 APPENDICES

- Appendix A** Discharge Permits RM10.308.01 and RM10.308.02
- Appendix B** Wastewater Quality Monitoring Results
- Appendix C** Watercare Laboratory Results
- Appendix D** Daily Wastewater Flow Results
- Appendix E** Nitrogen Mass Balance Spreadsheet
- Appendix F** Maintenance Records
- Appendix G** Hawea River Water Sampling Results
- Appendix H** ERPRO (2019) QLDC Lake Hawea WWTP Nitrogen Reduction Implementation



APPENDIX A

Discharge Permits RM10.308.01 and RM10.308.02



Discharge to Air Permit RM10.308.01

Conditions

Specific

1. This consent shall only be exercised in conjunction with Discharge Permit RM10.308.02.
2. The discharge to air shall be as described in the consent application submitted to the Consent Authority on 31 August 2010 and any subsequent information provided
3. Wind cloth shall be installed on the western, southern and eastern-most boundaries of the area on which treated wastewater is to be applied by spray irrigation. This wind cloth shall be maintained until the screen foliage required under Condition 4 is fully established.
4. Suitable screening foliage, that shall be at least 3 metres high but not exceed 6 metres in height, shall be planted on the western, southern and eastern-most boundaries of the area on which treated wastewater is applied by spray irrigation.
5. A weather station shall be installed in an appropriate location to record, as a minimum, rainfall and wind conditions at the site where treated wastewater is to be applied by spray irrigation.
6. The spray irrigation system shall not be operated in conditions where wind speed, as measured at the on-site station installed under Condition 5, exceeds 29.9 km/hour;

Performance Monitoring

7. The consent holder shall keep a record of any complaints received regarding discharges of odour from the site. The record shall, as a minimum, include the following:
 - (a) The time and place at which the complaint was generated;
 - (b) The nature of the complaint;
 - (c) Operating conditions at the time of the complaint, including any malfunctioning or breakdown of control equipment;
 - (d) Wind and weather conditions at the time of the complaint; and
 - (e) Corrective action taken by the consent holder to minimise the risk and extent of the recurrence of the causes of the complaint.

The consent holder shall submit a copy of the written record of the complaint to the Consent Authority within two weeks after any complaint occurring, together with the details of the corrective actions taken.

General

8. There shall be no discharge of odour, as a result of the exercise of this consent, that is noxious, dangerous, offensive or objectionable to the extent that it causes an adverse effect beyond the boundary of the site, in the opinion of an authorised officer of the Consent Authority.
9. The Consent Authority may, in accordance with Sections 128 and 129 of the Resource Management Act 1991, serve notice on the consent holder of its intention to review the conditions of this consent within three months of each anniversary of the commencement of this consent, for the purpose of:
 - (a) Determining whether the conditions of this consent are adequate to deal with any adverse effect on the environment which may arise from the exercise of the consent and which it is appropriate to deal with at a later stage, or which become evident after the date of commencement of the consent; or



- (b) Ensuring the conditions of this consent are consistent with any National Environmental Standards; or
- (c) Requiring the consent holder to adopt the best practicable option to remove or reduce any adverse effect on the environment arising as a result of the exercise of this consent.

Notes to Consent Holder

1. *If you require a replacement consent/permit upon the expiry date of this permit, any new application should be lodged at least 6 months prior to the expiry date of this permit. Applying at least 6 months before the expiry date may enable you to continue to exercise this permit until a decision is made, and any appeals are resolved, on the replacement application.*

Discharge to Land Permit RM10.308.02

Conditions

Specific

1. The discharge shall only be treated domestic wastewater, as described in the consent application submitted to the Consent Authority on 31 August 2010 and any subsequent information provided.
2. The volume of effluent discharged shall not exceed 775 cubic metres per day.
3. The distance the site boundary from any part of the wastewater treatment and disposal system shall no less than 5 metres.
4. By no later than 1 December 2012, the consent holder shall ensure that the trench utilised for wastewater disposal:
 - a) is at least 150 metres long and 2 m wide in total; and
 - b) is intermittently dosed; and
 - c) is not used for the disposal of wastewater for more than 4 months in total in any one calendar year.
5. By no later than 1 December 2012, the consent holder shall install and commission a spray irrigation system for the land application of treated wastewater. The spray irrigation system shall meet the following criteria:
 - (a) The total area on which treated wastewater is applied by spray irrigation shall be no less than 2.33 hectares;
 - (b) Treated wastewater shall be applied evenly by spray irrigation to the area defined in Appendix I only;
 - (c) The area on which treated wastewater is applied by spray irrigation shall be fenced with a 2-metre-high deer fence with appropriate signage warning the general public of the hazard;
 - (d) A weather station shall be installed in an appropriate location to record, as a minimum, rainfall and wind conditions at the site where treated wastewater is to be applied by spray irrigation;
 - (e) Wastewater shall not be applied to land by spray irrigation system during the hours outside of 11 pm to 5 am; (f) Nozzle pressure must not exceed 400 kilopascals (kPa);
 - (g) There shall be no irrigation of treated wastewater using K-Line irrigation systems.
6. The area on which treated wastewater is to be applied using spray irrigation shall be planted in high growth and nitrogen uptake vegetation (such as Lucerne or Ryegrass) and



shall be managed as far as practicably possible to optimise nutrient removal. A minimum of three harvests per year shall be undertaken.

7. The total nitrogen applied to the spray irrigation area shall not exceed 1,223 kilograms of nitrogen per hectare per year.

Performance Monitoring

8. The treatment and disposal system shall be constructed and installed in accordance with the details and plans supplied with the consent application submitted to the Consent Authority on 31 August 2010, and attached to this consent as Appendix I.
9. The consent holder shall install a flow meter on the outlet pipe from the treatment system and continually measure and record the daily volume (based on a no more than weekly average) of effluent being discharged to the disposal field. The consent holder shall forward the record for the previous 12-month period to the Consent Authority by 1 December each year, and upon request.
10. (a) From the first exercise of this consent, the consent holder shall collect representative samples of the treated wastewater from the outlet of the oxidation pond in the last week of each month. The samples shall be analysed for:
 - (i) Five-day total biochemical oxygen demand (BOD₅); and
 - (ii) Total suspended solids; and (iii) Total nitrogen; and (iv) Total Ammoniacal nitrogen; and (v) Total phosphorous; and (vi) *Escherichia coli*.

(b) From the first exercise of this consent, wastewater discharged from the oxidation pond shall comply with the following criteria:

| | Mean* | 95 th Percentile (mg/L) * |
|---------------------|-----------|--------------------------------------|
| Ammoniacal Nitrogen | 25 (mg/L) | 30 (mg/L) |
| Total Nitrogen | 35 (mg/L) | 40 (mg/L) |
| Total Phosphorous | 8 (mg/L) | 10 (mg/L) |
| Faecal Coliforms | - | 2.5 x 10 ⁵ cfu/100 mL |

*The mean and 95th percentile apply to a rolling 12-month period.

- (c) The analytical sample results from the sampling under Condition 9(a) of this consent shall be submitted to the Consent Authority by 1 December each year, and upon request.
11. All sampling techniques shall be acceptable to the Consent Authority. All analysis carried out in connection with this consent shall be performed by a laboratory that meets ISO 17025 standards, or otherwise as specifically approved by the Consent Authority.
12. The following information shall be provided in writing to the Consent Authority by 1 December each year, and upon request, following the commencement of the exercise of the consent:
 - (a) The nitrogen mass balance for the spray irrigation land application area, which shall be determined annually. The nitrogen mass balance shall consist as a minimum the total nitrogen applied to land and crop removal of nitrogen.
 - (b) The total nitrogen applied to the spray irrigation land shall be estimated from the total volume of effluent applied and the average of monthly concentration of total nitrogen in the land applied effluent.
 - (c) The crop removal of nitrogen from the spray irrigation land shall be estimated by obtaining dry matter content and total nitrogen content after each crop/plant harvest.
 - (d) The nitrogen mass balance from Condition 12(a) and any other factors such as ammonia volatilisation and denitrification shall be used to calculate the mass of nitrogen leached from the site, using a model acceptable to the Consent Authority



13. The consent holder shall forward an annual report in writing to the Consent Authority by 1 December each year. The annual report shall cover the preceding 12-month period (from 1 December the preceding year until 30 November of the current year) and shall report on compliance with this consent. As a minimum, the report shall include:
- (a) A summary of all analytical results for the year; and
 - (b) A summary of the year's monitoring results, in context of previous years' results; and
 - (c) Comments on compliance with the conditions of this discharge permit; and
 - (d) A summary of any complaints received, the validity of each complaint and the corrective action taken; and
 - (e) A summary of any malfunctions of breakdowns and the corrective action taken; and
 - (f) Details of the cut and carry operation, including the calculations for nitrogen loading in the spray irrigation land, number of harvests, dry matter and total nitrogen content of the harvest and nitrogen balance for this site.
 - (g) Any other issues considered relevant by the consent holder.
14. By no later than 1 December 2012, the consent holder shall prepare and forward to the Consent Authority an Operations and Management Manual for the wastewater treatment and disposal system to ensure its effective and efficient operation at all times. The system shall be operated in accordance with this manual, which shall be updated as appropriate. The manual and include, as a minimum,
- (a) A brief description of the treatment and disposal system, including a site map indicating the location of the treatment and disposal system, points of discharge and any monitoring sites;
 - (b) Key operational matters, including weekly, monthly and annual maintenance checks;
 - (c) Monitoring requirements and procedures including a nitrogen balance sheet for the purpose of managing nitrogen inputs and outputs including nitrogen leaching losses;
 - (d) A management plan for the cut and carry operation including procedures for harvesting grass from the site, and maximising grass growth and nitrogen uptake by grass such as soil tests, supplementary nutrient additions and pest and weed control;
 - (e) Management and dosing of trenches
 - (f) Contingency plans in the event of system malfunctions or breakdowns; and
 - (g) The means of receiving and dealing with any complaints; and
 - (h) Emergency contact phone numbers.

General

15. No ponding or surface run-off of effluent shall occur as a result of the exercise of this consent.
16. There shall be no odour emission resulting from the treatment and disposal system that is offensive or objectionable to such an extent that it has an adverse effect on the environment beyond the boundary of the property on which the consent is exercised
17. This permit does not authorise the discharge of sludge to land or water.
18. If the consent holder:
- (a) discovers koiwi tangata (human skeletal remains), waahi taoka (resources of importance), waahi tapu (places or features of special significance) or other Maori artefact material, the consent holder shall without delay:
 - (i) notify the Consent Authority, Tangata whenua and New Zealand Historic Places Trust and in the case of skeletal remains, the New Zealand Police.
 - (ii) stop work within the immediate vicinity of the discovery to allow a site inspection by the New Zealand Historic Places Trust and the appropriate runanga and their advisors, who shall determine whether the discovery is likely to be extensive, if a thorough site investigation is required, and whether an Archaeological Authority is required.
- Any koiwi tangata discovered shall be handled and removed by tribal elders responsible for the tikanga (custom) appropriate to its removal or preservation.



Site work shall recommence following consultation with the Consent Authority, the New Zealand Historic Places Trust, Tangata whenua, and in the case of skeletal remains, the New Zealand Police, provided that any relevant statutory permissions have been obtained.

(b) discovers any feature or archaeological material that predates 1900, or heritage material, or disturbs a previously unidentified archaeological or heritage site, the consent holder shall without delay:

(i) stop work within the immediate vicinity of the discovery or disturbance and

(ii) advise the Consent Authority, the New Zealand Historic Places Trust, and in the case of Maori features or materials, the Tangata whenua, and if required, shall make an application for an Archaeological Authority pursuant to the Historic Places Act 1993 and

(iii) arrange for a suitably qualified archaeologist to undertake a survey of the site.

Site work shall recommence following consultation with the Consent Authority.

19. The Consent Authority may, in accordance with Sections 128 and 129 of the Resource Management Act 1991, serve notice on the consent holder of its intention to review the conditions of this consent within three months of each anniversary of the commencement of this consent, for the purpose of:

(a) determining whether the conditions of this consent are adequate to deal with any adverse effect on the environment which may arise from the exercise of the consent and which it is appropriate to deal with at a later stage, or which become evident after the date of commencement of the consent; or

(b) ensuring the conditions of this consent are consistent with any National Environmental Standards; or


(c) requiring the consent holder to adopt the best practicable option, in order to remove or reduce any adverse effect on the environment arising as a result of the exercise of this consent.

Notes to Consent Holder

1. *If you require a replacement consent/permit upon the expiry date of this permit, any new application should be lodged at least 6 months prior to the expiry date of this permit. Applying at least 6 months before the expiry date may enable you to continue to exercise this permit until a decision is made, and any appeals are resolved, on the replacement application.*



Appendix I – Area on which Treated Wastewater is to be applied using Spray Irrigation





APPENDIX B

Wastewater Quality Monitoring Results



| | Total Suspended Solids g/m ³ | | BOD ₅ g/m ³ | | Total Phosphorus mg/L | | | Total Nitrogen g/m ³ | | | Ammoniacal Nitrogen g/m ³ | | | E. Coli cfu/100 mL | | |
|------------|--|------------------------------|--------------------------------------|------------------------------|--------------------------|------------------------------|--|------------------------------------|------------------------------|--|---|------------------------------|--|-----------------------|------------------------------|--|
| | Actual Measured | Rolling 12 Month Annual Mean | Actual Measured | Rolling 12 Month Annual Mean | Actual Measured | Rolling 12 Month Annual Mean | Rolling 12 Month 95 th percentile | Actual Measured | Rolling 12 Month Annual Mean | Rolling 12 Month 95 th percentile | Actual Measured | Rolling 12 Month Annual Mean | Rolling 12 Month 95 th percentile | Actual Measured | Rolling 12 Month Annual Mean | Rolling 12 Month 95 th percentile |
| | | | | | | | | | | | | | | | | |
| | | | | | | 8 | 10 | | 35 | 40 | | 25 | 30 | | | 250,000 |
| 20/12/2017 | 49 | 130 | 19 | 30 | 8.2 | 7 | 8 | 40 | 37 | 64 | 30 | 23 | 44 | 11,000 | 47,417 | 123,500 |
| 23/01/2018 | 130 | 131 | 35 | 31 | 7.7 | 7 | 8 | 22 | 37 | 64 | 8 | 23 | 44 | 36,000 | 49,833 | 123,500 |
| 28/02/2018 | 230 | 135 | 74 | 33 | 6.4 | 7 | 8 | 31 | 38 | 64 | 0 | 23 | 44 | 130,000 | 55,583 | 134,500 |
| 20/03/2018 | 130 | 135 | 37 | 33 | 7.5 | 7 | 8 | 27 | 39 | 64 | 1 | 23 | 44 | 55,000 | 58,000 | 134,500 |
| 20/04/2018 | 120 | 115 | 51 | 35 | 7.9 | 7 | 8 | 29 | 40 | 64 | 2 | 22 | 44 | 5,600 | 53,800 | 134,500 |
| 21/05/2018 | 64 | 116 | 28 | 36 | 6.3 | 7 | 8 | 27 | 39 | 64 | 16 | 21 | 44 | 37,000 | 53,550 | 134,500 |
| 20/06/2018 | 32 | 115 | 24 | 36 | 6.0 | 7 | 8 | 34 | 38 | 64 | 30 | 21 | 44 | 5,200 | 52,400 | 134,500 |
| 26/07/2018 | 48 | 112 | 25 | 36 | 6.5 | 7 | 8 | 45 | 36 | 53 | 38 | 21 | 43 | 3,000 | 40,983 | 119,000 |
| 21/08/2018 | 75 | 110 | 19 | 35 | 6.5 | 7 | 8 | 49 | 37 | 54 | 41 | 21 | 45 | 4,300 | 37,342 | 119,000 |
| 20/09/2018 | 140 | 112 | 64 | 37 | 6.8 | 7 | 8 | 52 | 37 | 56 | 36 | 21 | 45 | 66,000 | 33,675 | 94,800 |
| 16/10/2018 | 130 | 112 | 41 | 38 | 7.2 | 7 | 8 | 58 | 37 | 55 | 43 | 20 | 42 | 83,000 | 38,508 | 104,150 |
| 20/11/2018 | 88 | 103 | 18 | 36 | 7.7 | 7 | 8 | 57 | 39 | 57 | 43 | 24 | 43 | 22,000 | 38,175 | 104,150 |
| 20/12/2018 | 59 | 104 | 32 | 37 | 7.8 | 7 | 8 | 55 | 41 | 57 | 38 | 25 | 43 | 240,000 | 57,258 | 179,500 |
| 23/01/2019 | 74 | 99 | 28 | 37 | 11.0 | 7 | 9 | 65 | 44 | 61 | 43 | 28 | 43 | 20,000 | 55,925 | 179,500 |
| 21/02/2019 | 59 | 85 | 23 | 33 | 8.9 | 8 | 10 | 56 | 46 | 61 | 42 | 31 | 43 | 20,000 | 46,758 | 153,650 |
| 20/03/2019 | 140 | 86 | 22 | 31 | 7.7 | 8 | 10 | 52 | 48 | 61 | 38 | 34 | 43 | 50,000 | 46,342 | 153,650 |
| 23/04/2019 | 110 | 85 | 31 | 30 | 6.7 | 7 | 10 | 22 | 48 | 61 | 4 | 34 | 43 | 110,000 | 55,042 | 168,500 |
| 20/05/2019 | 86 | 87 | 48 | 31 | 6.1 | 7 | 10 | 27 | 48 | 61 | 13 | 34 | 43 | 9,800 | 52,775 | 168,500 |
| 20/06/2019 | 56 | 89 | 8.1 | 30 | 6.2 | 7 | 10 | 39 | 48 | 61 | 30 | 34 | 43 | 4,900 | 52,750 | 168,500 |
| 23/07/2019 | 35 | 88 | 36 | 31 | 6.6 | 7 | 10 | 46 | 48 | 61 | 38 | 34 | 43 | 95,000 | 60,417 | 168,500 |
| 20/08/2019 | 55 | 86 | 34 | 32 | 6.8 | 7 | 10 | 55 | 49 | 61 | 39 | 34 | 43 | 66,000 | 65,558 | 168,500 |
| 19/09/2019 | 280 | 98 | 34 | 30 | 7.3 | 8 | 10 | 110 | 54 | 85 | 43 | 34 | 43 | 38,000 | 63,225 | 168,500 |
| 21/10/2019 | 140 | 99 | 39 | 29 | 8.0 | 8 | 10 | 62 | 54 | 85 | 42 | 34 | 43 | 31,000 | 58,892 | 168,500 |
| 27/11/2019 | 88 | 99 | 15 | 29 | 7.7 | 8 | 10 | 71 | 55 | 89 | 50 | 35 | 46 | 3,000 | 57,308 | 168,500 |



APPENDIX C

Watercare Laboratory Results

Certificate of Analysis

Laboratory Reference: 181220-142

| | | | |
|--------------------------|--|---------------------------|--------------------|
| Attention: | Operations . | Final Report: | 299666-0 |
| Client: | VEOLIA WATER | Report Issue Date: | 08-Jan-2019 |
| Address: | | Received Date: | 21-Dec-2018 |
| Client Reference: | Hawea Ponds Monthly December 2018 | Quote Reference : | 42 |
| Purchase Order: | PO92832 | | |

Sample Details

WATERS

| | |
|--------------------------|----------------------------------|
| Lab Sample ID: | 181220-142-1 |
| Client Sample ID: | |
| Sample Date/Time: | 20/12/2018 |
| Description: | Hawea Effluent (RM 10.308.02) |

General Testing

| | | |
|----------------------------|------|-----|
| Ammoniacal Nitrogen (as N) | mg/L | 38 |
| CBOD5 | mg/L | 32 |
| Total Nitrogen (as N) | mg/L | 55 |
| Total Phosphorus (as P) | mg/L | 7.8 |
| Total Suspended Solids | mg/L | 59 |

Microbiology

Escherichia coli by Membrane Filtration

| | | |
|------------------|------------|--------|
| Escherichia coli | cfu/100 mL | 240000 |
|------------------|------------|--------|

*Results marked with * are not accredited to International Accreditation New Zealand*

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|---|------------|---------|----------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | HMSO (1981) ISBN 0117516139 | 0.4 mg/L | All | Auckland |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 by Electrode | APHA (online edition) 5210 B (modified) | 0.5 mg/L | All | Auckland |
| Total Nitrogen (as N) by Persulphate Digestion and Flow Analysis | APHA (online edition) 4500-P J (modified), 4500-NO3 I | 0.010 mg/L | All | Auckland |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J (modified) | 0.004 mg/L | All | Auckland |
| Total Suspended Solids by Gravimetry | In House based on APHA (online edition) 2540 D, E | 1 mg/L | All | Auckland |

Microbiology

Escherichia coli by Membrane Filtration

| | | | | |
|------------------|-------------------|--------------|-----|----------|
| Escherichia coli | USEPA Method 1603 | 2 cfu/100 mL | All | Auckland |
|------------------|-------------------|--------------|-----|----------|

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher. For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited.

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Report Signatory 08/01/2019

A handwritten signature in blue ink, appearing to read 'Marina Fisher'.

Marina Fisher
KTP Signatory

Certificate of Analysis

Laboratory Reference: 190123-106

| | | | |
|--------------------------|---|---------------------------|--------------------|
| Attention: | Operations . | Final Report: | 303185-0 |
| Client: | VEOLIA WATER | Report Issue Date: | 01-Feb-2019 |
| Address: | | Received Date: | 24-Jan-2019 |
| Client Reference: | Hawea Ponds Monthly January 2019 | Quote Reference : | 42 |
| Purchase Order: | PO92832 | | |

Sample Details

WATERS

| | |
|--------------------------|----------------------------------|
| Lab Sample ID: | 190123-106-1 |
| Client Sample ID: | |
| Sample Date/Time: | 23/01/2019 |
| Description: | Hawea Effluent (RM 10.308.02) |

General Testing

| | | |
|----------------------------|------|----|
| Ammoniacal Nitrogen (as N) | mg/L | 43 |
| CBOD5 | mg/L | 28 |
| Total Nitrogen (as N) | mg/L | 65 |
| Total Phosphorus (as P) | mg/L | 11 |
| Total Suspended Solids | mg/L | 74 |

Microbiology

Escherichia coli by Membrane Filtration

| | | |
|------------------|------------|-------|
| Escherichia coli | cfu/100 mL | 20000 |
|------------------|------------|-------|

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|---|------------|---------|----------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | HMSO (1981) ISBN 0117516139 | 0.4 mg/L | All | Auckland |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 by Electrode | APHA (online edition) 5210 B (modified) | 0.5 mg/L | All | Auckland |
| Total Nitrogen (as N) by Persulphate Digestion and Flow Analysis | APHA (online edition) 4500-P J (modified), 4500-NO3 I | 0.010 mg/L | All | Auckland |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J (modified) | 0.004 mg/L | All | Auckland |
| Total Suspended Solids by Gravimetry | In House based on APHA (online edition) 2540 D, E | 1 mg/L | All | Auckland |

Microbiology

Escherichia coli by Membrane Filtration

| | | | | |
|------------------|-------------------|--------------|-----|----------|
| Escherichia coli | USEPA Method 1603 | 2 cfu/100 mL | All | Auckland |
|------------------|-------------------|--------------|-----|----------|

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher.
For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited.

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Report Signatory 01/02/2019

A handwritten signature in blue ink, appearing to read 'Chandra Sharma'.

Chandra Sharma
KTP Signatory

Certificate of Analysis

Laboratory Reference: 190221-080

| | | | |
|--------------------------|--|---------------------------|--------------------|
| Attention: | Operations . | Final Report: | 306977-0 |
| Client: | VEOLIA WATER | Report Issue Date: | 28-Feb-2019 |
| Address: | | Received Date: | 22-Feb-2019 |
| Client Reference: | Hawea Ponds Monthly February 2019 | Quote Reference : | 42 |
| Purchase Order: | PO7300051656 | | |

Sample Details

WATERS

| | |
|--------------------------|----------------------------------|
| Lab Sample ID: | 190221-080-1 |
| Client Sample ID: | |
| Sample Date/Time: | 21/02/2019 |
| Description: | Hawea Effluent (RM 10.308.02) |

General Testing

| | | |
|----------------------------|------|-----|
| Ammoniacal Nitrogen (as N) | mg/L | 42 |
| CBOD5 | mg/L | 23 |
| Total Nitrogen (as N) | mg/L | 56 |
| Total Phosphorus (as P) | mg/L | 8.9 |
| Total Suspended Solids | mg/L | 59 |

Microbiology

Escherichia coli by Membrane Filtration

| | | |
|------------------|------------|-------|
| Escherichia coli | cfu/100 mL | 20000 |
|------------------|------------|-------|

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|---|------------|---------|----------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | HMSO (1981) ISBN 0117516139 | 0.4 mg/L | All | Auckland |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 by Electrode | APHA (online edition) 5210 B (modified) | 0.5 mg/L | All | Auckland |
| Total Nitrogen (as N) by Persulphate Digestion and Flow Analysis | APHA (online edition) 4500-P J (modified), 4500-NO3 I | 0.010 mg/L | All | Auckland |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J (modified) | 0.004 mg/L | All | Auckland |
| Total Suspended Solids by Gravimetry | In House based on APHA (online edition) 2540 D, E | 1 mg/L | All | Auckland |

Microbiology

Escherichia coli by Membrane Filtration

| | | | | |
|------------------|-------------------|--------------|-----|----------|
| Escherichia coli | USEPA Method 1603 | 2 cfu/100 mL | All | Auckland |
|------------------|-------------------|--------------|-----|----------|

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher.
For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited .

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Report Signatory 28/02/2019

A handwritten signature in blue ink, appearing to read 'Chandra Sharma'.

Chandra Sharma
KTP Signatory

Certificate of Analysis

Laboratory Reference: 190320-131

| | | | |
|--------------------------|---------------------------------------|---------------------------|--------------------|
| Attention: | Operations . | Final Report: | 311088-0 |
| Client: | VEOLIA WATER | Report Issue Date: | 27-Mar-2019 |
| Address: | | Received Date: | 21-Mar-2019 |
| Client Reference: | Hawea Ponds Monthly March 2019 | Sampled By: | WLS |
| Purchase Order: | PO100467 | Quote Reference : | 42 |

Sample Details

WATERS

| | |
|--------------------------|----------------------------------|
| Lab Sample ID: | 190320-131-1 |
| Client Sample ID: | |
| Sample Date/Time: | 20/03/2019 |
| Description: | Hawea Effluent (RM 10.308.02) |

General Testing

| | | |
|----------------------------|------|-----|
| Ammoniacal Nitrogen (as N) | mg/L | 38 |
| CBOD5 | mg/L | 22 |
| Total Nitrogen (as N) | mg/L | 52 |
| Total Phosphorus (as P) | mg/L | 7.7 |
| Total Suspended Solids | mg/L | 140 |

Microbiology

Escherichia coli by Membrane Filtration

| | | |
|------------------|------------|-------|
| Escherichia coli | cfu/100 mL | 50000 |
|------------------|------------|-------|

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|---|------------|---------|----------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | HMSO (1981) ISBN 0117516139 | 0.4 mg/L | All | Auckland |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 by Electrode | APHA (online edition) 5210 B (modified) | 0.5 mg/L | All | Auckland |
| Total Nitrogen (as N) by Persulphate Digestion and Flow Analysis | APHA (online edition) 4500-P J (modified), 4500-NO3 I | 0.010 mg/L | All | Auckland |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J (modified) | 0.004 mg/L | All | Auckland |
| Total Suspended Solids by Gravimetry | In House based on APHA (online edition) 2540 D, E | 1 mg/L | All | Auckland |

Microbiology

Escherichia coli by Membrane Filtration

| | | | | |
|------------------|-------------------|--------------|-----|----------|
| Escherichia coli | USEPA Method 1603 | 2 cfu/100 mL | All | Auckland |
|------------------|-------------------|--------------|-----|----------|

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher.
For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited.

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Report Signatory 27/03/2019

A handwritten signature in blue ink, appearing to read 'Alice Liaw', with a horizontal line extending to the right.

Alice Liaw
KTP Signatory

Certificate of Analysis

Laboratory Reference: 190423-089

| | | | |
|--------------------------|---------------------------------------|---------------------------|--------------------|
| Attention: | Operations . | Final Report: | 315210-0 |
| Client: | VEOLIA WATER | Report Issue Date: | 29-Apr-2019 |
| Address: | | Received Date: | 24-Apr-2019 |
| Client Reference: | Hawea Ponds Monthly April 2019 | Sampled By: | WLS |
| Purchase Order: | PO7300058275 | Quote Reference : | 42 |

Sample Details

WATERS

| | |
|--------------------------|----------------------------------|
| Lab Sample ID: | 190423-089-1 |
| Client Sample ID: | |
| Sample Date/Time: | 23/04/2019 |
| Description: | Hawea Effluent (RM 10.308.02) |

General Testing

| | | |
|----------------------------|------|-----|
| Ammoniacal Nitrogen (as N) | mg/L | 3.8 |
| CBOD5 | mg/L | 31 |
| Total Nitrogen (as N) | mg/L | 22 |
| Total Phosphorus (as P) | mg/L | 6.7 |
| Total Suspended Solids | mg/L | 110 |

Microbiology

Escherichia coli by Membrane Filtration

| | | |
|------------------|------------|--------|
| Escherichia coli | cfu/100 mL | 110000 |
|------------------|------------|--------|

*Results marked with * are not accredited to International Accreditation New Zealand*

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|---|------------|---------|----------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | HMSO (1981) ISBN 0117516139 | 0.4 mg/L | All | Auckland |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 by Electrode | APHA (online edition) 5210 B (modified) | 0.5 mg/L | All | Auckland |
| Total Nitrogen (as N) by Persulphate Digestion and Flow Analysis | APHA (online edition) 4500-P J (modified), 4500-NO3 I | 0.010 mg/L | All | Auckland |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J (modified) | 0.004 mg/L | All | Auckland |
| Total Suspended Solids by Gravimetry | In House based on APHA (online edition) 2540 D, E | 1 mg/L | All | Auckland |

Microbiology

Escherichia coli by Membrane Filtration

| | | | | |
|------------------|-------------------|--------------|-----|----------|
| Escherichia coli | USEPA Method 1603 | 2 cfu/100 mL | All | Auckland |
|------------------|-------------------|--------------|-----|----------|

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher. For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited .

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Report Signatory 29/04/2019

A handwritten signature in blue ink, appearing to read 'Chandra Sharma'.

Chandra Sharma
KTP Signatory

Certificate of Analysis

Laboratory Reference: 190521-121

| | | | |
|--------------------------|---|---------------------------|--------------------|
| Attention: | Jennifer McGirr | Final Report: | 319344-0 |
| Client: | QUEENSTOWN LAKE DISTRICT COUNCIL | Report Issue Date: | 27-May-2019 |
| Address: | PO Box 50072, Queenstown, 9348 | Received Date: | 21-May-2019 |
| Client Reference: | Hawea River | Sampled By: | Watercare |
| Purchase Order: | 51CA23B/15708 | Quote Reference : | 10284 |

Sample Details

| | WATERS | WATERS |
|--------------------------|-------------------------|---------------------------|
| Lab Sample ID: | 190521-121-1 | 190521-121-2 |
| Client Sample ID: | | |
| Sample Date/Time: | 20/05/2019 12:10 | 20/05/2019 11:50 |
| Description: | Hawea River Upstream | Hawea River Downstream |

General Testing

| | mg/L | <0.01 | <0.01 |
|--------------------------------------|---------|--------|--------|
| Ammoniacal Nitrogen (as N) | mg/L | <0.01 | <0.01 |
| CBOD5 (as O2) | mg/L | 3.0 | 2.9 |
| Dissolved Reactive Phosphorus (as P) | mg/L | <0.005 | <0.005 |
| pH (at room temp c. 20 °C) | pH unit | 7.66 | 7.65 |
| Total Nitrogen (as N) | mg/L | 0.05 | 0.04 |
| Total Oxidised Nitrogen (as N) | mg/L | <0.01 | <0.01 |
| Total Phosphorus (as P) | mg/L | <0.01 | <0.01 |
| Total Suspended Solids | mg/L | <2.5 | <2.5 |

Microbiology

Escherichia coli by MPN(Colilert-18)

| Escherichia coli (Colilert-18) | MPN/100 mL | <10 | 10 |
|--------------------------------|------------|-----|----|
| | | | |

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|--|-------------|---------|--------------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | ISBN 0117516139 (modified) | 0.010 mg/L | All | Invercargill |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 (as O2) by Electrode | APHA (online edition) 5210 B | 2 mg/L | All | Invercargill |
| Dissolved Reactive Phosphorus (as P) by Colorimetry/Discrete Analyser | APHA (online edition) 4500-P E | 0.005 mg/L | All | Invercargill |
| pH (at room temp c. 20 °C) by Electrode | APHA (online edition) 4500-H B (Tested beyond 15 minute APHA holding time) | 0.1 pH unit | All | Invercargill |
| Total Nitrogen (as N) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J, 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Oxidised Nitrogen (as N) by Colorimetry/Discrete Analyser | APHA (online edition) 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P B, J (modified) | 0.010 mg/L | All | Invercargill |
| Total Suspended Solids by Gravimetry | APHA (online edition) 2540 D | 2.5 mg/L | All | Invercargill |

Microbiology

Escherichia coli by MPN(Colilert-18)

| Escherichia coli (Colilert-18) | APHA (online edition) 9223 B Colilert Quantitray | 1 MPN/100 mL | All | Invercargill |
|--------------------------------|--|--------------|-----|--------------|
| | | | | |

Preparations

| Membrane Filtration (0.45 µm) | APHA (online edition) 4500-P B (preliminary filtration) | All | Invercargill |
|-------------------------------|---|-----|--------------|
| | | | |

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher. For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited.

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Report Signatory 27/05/2019

A handwritten signature in black ink, appearing to read 'Tonia Bulling', written over a light grey rectangular background.

Tonia Bulling
KTP Signatory

Certificate of Analysis

Laboratory Reference: 190520-158

| | | | |
|--------------------------|-------------------------------------|---------------------------|--------------------|
| Attention: | Operations . | Final Report: | 319460-0 |
| Client: | VEOLIA WATER | Report Issue Date: | 27-May-2019 |
| Address: | | Received Date: | 21-May-2019 |
| Client Reference: | Hawea Ponds Monthly May 2019 | Sampled By: | WLS |
| Purchase Order: | PO7300060462 | Quote Reference : | 42 |

Sample Details

WATERS

| | |
|--------------------------|----------------------------------|
| Lab Sample ID: | 190520-158-1 |
| Client Sample ID: | |
| Sample Date/Time: | 20/05/2019 |
| Description: | Hawea Effluent (RM 10.308.02) |

General Testing

| | | |
|----------------------------|------|-----|
| Ammoniacal Nitrogen (as N) | mg/L | 13 |
| CBOD5 | mg/L | 48 |
| Total Nitrogen (as N) | mg/L | 27 |
| Total Phosphorus (as P) | mg/L | 6.1 |
| Total Suspended Solids | mg/L | 86 |

Microbiology

Escherichia coli by Membrane Filtration

| | | |
|------------------|------------|------|
| Escherichia coli | cfu/100 mL | 9800 |
|------------------|------------|------|

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|---|------------|---------|----------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | HMSO (1981) ISBN 0117516139 | 0.4 mg/L | All | Auckland |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 by Electrode | APHA (online edition) 5210 B (modified) | 0.5 mg/L | All | Auckland |
| Total Nitrogen (as N) by Persulphate Digestion and Flow Analysis | APHA (online edition) 4500-P J (modified), 4500-NO3 I | 0.010 mg/L | All | Auckland |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J (modified) | 0.004 mg/L | All | Auckland |
| Total Suspended Solids by Gravimetry | In House based on APHA (online edition) 2540 D, E | 1 mg/L | All | Auckland |

Microbiology

Escherichia coli by Membrane Filtration

| | | | | |
|------------------|-------------------|--------------|-----|----------|
| Escherichia coli | USEPA Method 1603 | 2 cfu/100 mL | All | Auckland |
|------------------|-------------------|--------------|-----|----------|

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher.
For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited .

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Report Signatory 27/05/2019

A handwritten signature in blue ink, appearing to read 'Chandra Sharma'.

Chandra Sharma
KTP Signatory

Certificate of Analysis

Laboratory Reference: 190620-090

| | | | |
|--------------------------|---|---------------------------|--------------------|
| Attention: | Jennifer McGirr | Final Report: | 323675-0 |
| Client: | QUEENSTOWN LAKE DISTRICT COUNCIL | Report Issue Date: | 28-Jun-2019 |
| Address: | PO Box 50072, Queenstown, 9348 | Received Date: | 21-Jun-2019 |
| Client Reference: | Hawea River | Sampled By: | Watercare |
| Purchase Order: | 51CA23B/15708 | Quote Reference : | 10284 |

Sample Details

| | WATERS | WATERS |
|--------------------------|-------------------------|---------------------------|
| Lab Sample ID: | 190620-090-1 | 190620-090-2 |
| Client Sample ID: | | |
| Sample Date/Time: | 20/06/2019 | 20/06/2019 |
| Description: | Hawea River Upstream | Hawea River Downstream |

General Testing

| | mg/L | <0.01 | <0.01 |
|--------------------------------------|---------|--------|-------|
| Ammoniacal Nitrogen (as N) | mg/L | <2.0 | <2.0 |
| CBOD5 (as O2) | mg/L | <0.005 | 0.008 |
| Dissolved Reactive Phosphorus (as P) | mg/L | | |
| pH (at room temp c. 20 °C) | pH unit | 7.55 | 7.50 |
| Total Nitrogen (as N) | mg/L | 0.06 | 0.14 |
| Total Oxidised Nitrogen (as N) | mg/L | <0.01 | <0.01 |
| Total Phosphorus (as P) | mg/L | <0.01 | <0.01 |
| Total Suspended Solids | mg/L | 3.4 | <2.5 |

Microbiology

Escherichia coli by MPN(Colilert-18)

| Escherichia coli (Colilert-18) | MPN/100 mL | <10 | 41 |
|--------------------------------|------------|-----|----|
| | | | |

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|--|-------------|---------|--------------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | ISBN 0117516139 (modified) | 0.010 mg/L | All | Invercargill |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 (as O ₂) by Electrode | APHA (online edition) 5210 B | 2 mg/L | All | Invercargill |
| Dissolved Reactive Phosphorus (as P) by Colorimetry/Discrete Analyser | APHA (online edition) 4500-P E | 0.005 mg/L | All | Invercargill |
| pH (at room temp c. 20 °C) by Electrode | APHA (online edition) 4500-H B (Tested beyond 15 minute APHA holding time) | 0.1 pH unit | All | Invercargill |
| Total Nitrogen (as N) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J, 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Oxidised Nitrogen (as N) by Colorimetry/Discrete Analyser | APHA (online edition) 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P B, J (modified) | 0.010 mg/L | All | Invercargill |
| Total Suspended Solids by Gravimetry | APHA (online edition) 2540 D | 2.5 mg/L | All | Invercargill |

Microbiology

Escherichia coli by MPN(Colilert-18)

| Escherichia coli (Colilert-18) | APHA (online edition) 9223 B Colilert Quantitray | 1 MPN/100 mL | All | Invercargill |
|--------------------------------|--|--------------|-----|--------------|
| | | | | |

Preparations

| Membrane Filtration (0.45 µm) | APHA (online edition) 4500-P B (preliminary filtration) | All | Invercargill |
|-------------------------------|---|-----|--------------|
| | | | |

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher. For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited.

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Report Signatory 28/06/2019

A handwritten signature in blue ink that reads 'Michelle Donovan'.

Michelle Donovan
KTP Signatory

Certificate of Analysis

Laboratory Reference: 190620-089

| | | | |
|--------------------------|--------------------------------------|---------------------------|--------------------|
| Attention: | Operations . | Final Report: | 323566-0 |
| Client: | VEOLIA WATER | Report Issue Date: | 27-Jun-2019 |
| Address: | | Received Date: | 21-Jun-2019 |
| Client Reference: | Hawea Ponds Monthly June 2019 | Sampled By: | WLS |
| Purchase Order: | 109274 | Quote Reference : | 42 |

Sample Details

WATERS

| | |
|--------------------------|----------------------------------|
| Lab Sample ID: | 190620-089-1 |
| Client Sample ID: | |
| Sample Date/Time: | 20/06/2019 |
| Description: | Hawea Effluent (RM 10.308.02) |

General Testing

| | | |
|----------------------------|------|-----|
| Ammoniacal Nitrogen (as N) | mg/L | 30 |
| CBOD5 | mg/L | 8.1 |
| Total Nitrogen (as N) | mg/L | 39 |
| Total Phosphorus (as P) | mg/L | 6.2 |
| Total Suspended Solids | mg/L | 56 |

Microbiology

Escherichia coli by Membrane Filtration

| | | |
|------------------|------------|------|
| Escherichia coli | cfu/100 mL | 4900 |
|------------------|------------|------|

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|---|------------|---------|----------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | HMSO (1981) ISBN 0117516139 | 0.4 mg/L | All | Auckland |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 by Electrode | APHA (online edition) 5210 B (modified) | 0.5 mg/L | All | Auckland |
| Total Nitrogen (as N) by Persulphate Digestion and Flow Analysis | APHA (online edition) 4500-P J (modified), 4500-NO3 I | 0.010 mg/L | All | Auckland |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J (modified) | 0.004 mg/L | All | Auckland |
| Total Suspended Solids by Gravimetry | In House based on APHA (online edition) 2540 D, E | 1 mg/L | All | Auckland |

Microbiology

Escherichia coli by Membrane Filtration

| | | | | |
|------------------|-------------------|--------------|-----|----------|
| Escherichia coli | USEPA Method 1603 | 2 cfu/100 mL | All | Auckland |
|------------------|-------------------|--------------|-----|----------|

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher.
For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited .

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Report Signatory 27/06/2019

A handwritten signature in blue ink, appearing to read 'Alice Liaw', with a horizontal line extending to the right.

Alice Liaw
KTP Signatory

Certificate of Analysis

Laboratory Reference: 190723-094

| | | | |
|--------------------------|---------------------------------------|---------------------------|--------------------|
| Attention: | Jennifer McGirr | Final Report: | 327702-0 |
| Client: | QUEENSTOWN LAKE DISTRICT COUNC | Report Issue Date: | 30-Jul-2019 |
| Address: | PO Box 50072, Queenstown, 9348 | Received Date: | 24-Jul-2019 |
| Client Reference: | Hawea River | Sampled By: | Watercare |
| Purchase Order: | PO028787 | Quote Reference : | 10284 |

Sample Details

| | WATERS | WATERS |
|--------------------------|-------------------------|---------------------------|
| Lab Sample ID: | 190723-094-1 | 190723-094-2 |
| Client Sample ID: | | |
| Sample Date/Time | 23/07/2019 | 23/07/2019 |
| Description: | Hawea River Upstream | Hawea River Downstream |

General Testing

| | mg/L | <0.01 | <0.01 |
|--------------------------------------|---------|-------|--------|
| Ammoniacal Nitrogen (as N) | mg/L | <2.0 | <2.0 |
| CBOD5 (as O2) | mg/L | 0.005 | <0.005 |
| Dissolved Reactive Phosphorus (as P) | mg/L | 7.69 | 7.67 |
| pH (at room temp c. 20 °C) | pH unit | 0.07 | 0.08 |
| Total Nitrogen (as N) | mg/L | 0.02 | 0.02 |
| Total Oxidised Nitrogen (as N) | mg/L | <0.01 | <0.01 |
| Total Phosphorus (as P) | mg/L | <2.5 | <2.5 |
| Total Suspended Solids | mg/L | | |

Microbiology

Escherichia coli by MPN(Colilert-18)

| Escherichia coli (Colilert-18) | MPN/100 mL | <10 | <10 |
|--------------------------------|------------|-----|-----|
| | | | |

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|--|--------------|---------|--------------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | ISBN 0117516139 (modified) | 0.010 mg/L | All | Invercargill |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 (as O 2) by Electrode | APHA (online edition) 5210 B | 2 mg/L | All | Invercargill |
| Dissolved Reactive Phosphorus (as P) by Colorimetry/Discrete Analyser | APHA (online edition) 4500-P E | 0.005 mg/L | All | Invercargill |
| pH (at room temp c. 20 °C) by Electrode | APHA (online edition) 4500-H B (Tested beyond 15 minute APHA holding time) | 0.1 pH unit | All | Invercargill |
| Total Nitrogen (as N) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J, 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Oxidised Nitrogen (as N) by Colorimetry/Discrete Analyser | APHA (online edition) 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P B, J (modified) | 0.010 mg/L | All | Invercargill |
| Total Suspended Solids by Gravimetry | APHA (online edition) 2540 D | 2.5 mg/L | All | Invercargill |
| Microbiology | | | | |
| Escherichia coli by MPN(Colilert-18) | | | | |
| Escherichia coli (Colilert-18) | APHA (online edition) 9223 B Colilert Quantitray | 1 MPN/100 mL | All | Invercargill |
| Preparations | | | | |
| Membrane Filtration (0.45 µm) | APHA (online edition) 4500-P B (preliminary filtration) | | All | Invercargill |

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher.
For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited .

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Michelle Donovan
KTP Signatory



Auckland

52 Aintree Ave,
PO Box 107028,
Auckland Airport
Auckland, 2150

T: (09) 539 7600
F: (09) 539 7601

Queenstown

74 Glenda Drive,
PO Box 2614
Wakatipu
Queenstown,

T: (03) 409 0559

Invercargill

142 Esk Street
PO Box 747
Invercargill, 9840

T: (03) 214 4040
F: (03) 214 4041

Certificate of Analysis

Laboratory Reference: 190723-093

| | | | |
|--------------------------|--------------------------------------|---------------------------|--------------------|
| Attention: | Operations . | Final Report: | 327714-0 |
| Client: | VEOLIA WATER | Report Issue Date: | 30-Jul-2019 |
| Address: | | Received Date: | 24-Jul-2019 |
| Client Reference: | Hawea Ponds Monthly July 2019 | Sampled By: | WLS |
| Purchase Order: | PO112218 | Quote Reference : | 42 |

Sample Details

WATERS

| | |
|--------------------------|----------------------------------|
| Lab Sample ID: | 190723-093-1 |
| Client Sample ID: | |
| Sample Date/Time | 23/07/2019 |
| Description: | Hawea Effluent (RM 10.308.02) |

General Testing

| | | |
|----------------------------|------|-----|
| Ammoniacal Nitrogen (as N) | mg/L | 38 |
| CBOD5 (as O2) | mg/L | 36 |
| Total Nitrogen (as N) | mg/L | 46 |
| Total Phosphorus (as P) | mg/L | 6.6 |
| Total Suspended Solids | mg/L | 35 |

Microbiology

Escherichia coli by Membrane Filtration

| | | |
|------------------|------------|-------|
| Escherichia coli | cfu/100 mL | 95000 |
|------------------|------------|-------|

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|--|------------|---------|--------------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | ISBN 0117516139 (modified) | 0.010 mg/L | All | Invercargill |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 (as O2) by Electrode | APHA (online edition) 5210 B | 2 mg/L | All | Invercargill |
| Total Nitrogen (as N) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J, 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P B, J (modified) | 0.010 mg/L | All | Invercargill |
| Total Suspended Solids by Gravimetry | APHA (online edition) 2540 D | 2.5 mg/L | All | Invercargill |

Microbiology

Escherichia coli by Membrane Filtration

| | | | | |
|------------------|--------------------------|--------------|-----|--------------|
| Escherichia coli | USEPA Method 1603 (2002) | 2 cfu/100 mL | All | Invercargill |
|------------------|--------------------------|--------------|-----|--------------|

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher. For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited.

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Michelle Donovan
KTP Signatory



Auckland

52 Aintree Ave,
PO Box 107028,
Auckland Airport
Auckland, 2150

T: (09) 539 7600
F: (09) 539 7601

Queenstown

74 Glenda Drive,
PO Box 2614
Wakatipu
Queenstown,

T: (03) 409 0559

Invercargill

142 Esk Street
PO Box 747
Invercargill, 9840

T: (03) 214 4040
F: (03) 214 4041

Certificate of Analysis

Laboratory Reference: 190820-081

| | | | |
|--------------------------|---------------------------------------|---------------------------|--------------------|
| Attention: | Jennifer McGirr | Final Report: | 331932-0 |
| Client: | QUEENSTOWN LAKE DISTRICT COUNC | Report Issue Date: | 03-Sep-2019 |
| Address: | PO Box 50072, Queenstown, 9348 | Received Date: | 21-Aug-2019 |
| Client Reference: | Hawea River | Sampled By: | Watercare |
| Purchase Order: | PO028787 | Quote Reference : | 10284 |

Sample Details

| | WATERS | WATERS |
|--------------------------|-------------------------|---------------------------|
| Lab Sample ID: | 190820-081-1 | 190820-081-2 |
| Client Sample ID: | | |
| Sample Date/Time | 20/08/2019 | 20/08/2019 |
| Description: | Hawea River Upstream | Hawea River Downstream |

General Testing

| | mg/L | <0.01 | <0.01 |
|--------------------------------------|---------|--------|--------|
| Ammoniacal Nitrogen (as N) | mg/L | <2.0 | <2.0 |
| CBOD5 (as O2) | mg/L | <0.005 | <0.005 |
| Dissolved Reactive Phosphorus (as P) | mg/L | 7.70 | 7.59 |
| pH (at room temp c. 20 °C) | pH unit | 0.04 | 0.06 |
| Total Nitrogen (as N) | mg/L | 0.02 | 0.01 |
| Total Oxidised Nitrogen (as N) | mg/L | 0.02 | <0.01 |
| Total Phosphorus (as P) | mg/L | 3.9 | <2.5 |
| Total Suspended Solids | mg/L | | |

Microbiology

Escherichia coli by MPN(Colilert-18)

| Escherichia coli (Colilert-18) | MPN/100 mL | <10 | <10 |
|--------------------------------|------------|-----|-----|
| | | | |

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|--|-------------|---------|--------------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | ISBN 0117516139 (modified) | 0.010 mg/L | All | Invercargill |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 (as O 2) by Electrode | APHA (online edition) 5210 B | 2 mg/L | All | Invercargill |
| Dissolved Reactive Phosphorus (as P) by Colorimetry/Discrete Analyser | APHA (online edition) 4500-P E | 0.005 mg/L | All | Invercargill |
| pH (at room temp c. 20 °C) by Electrode | APHA (online edition) 4500-H B (Tested beyond 15 minute APHA holding time) | 0.1 pH unit | All | Invercargill |
| Total Nitrogen (as N) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J, 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Oxidised Nitrogen (as N) by Colorimetry/Discrete Analyser | APHA (online edition) 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P B, J (modified) | 0.010 mg/L | All | Invercargill |
| Total Suspended Solids by Gravimetry | APHA (online edition) 2540 D | 2.5 mg/L | All | Invercargill |

Microbiology

Escherichia coli by MPN(Colilert-18)

| Escherichia coli (Colilert-18) | APHA (online edition) 9223 B Colilert Quantitray | 1 MPN/100 mL | All | Invercargill |
|--------------------------------|--|--------------|-----|--------------|
| | | | | |

Preparations


| Membrane Filtration (0.45 µm) | APHA (online edition) 4500-P B (preliminary filtration) | | All | Invercargill |
|-------------------------------|---|--|-----|--------------|
| | | | | |

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher.
For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited .

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Tonia Bulling
KTP Signatory



Auckland

52 Aintree Ave,
PO Box 107028,
Auckland Airport
Auckland, 2150

T: (09) 539 7600
F: (09) 539 7601

Queenstown

74 Glenda Drive,
PO Box 2614
Wakatipu
Queenstown,

T: (03) 409 0559

Invercargill

142 Esk Street
PO Box 747
Invercargill, 9840

T: (03) 214 4040
F: (03) 214 4041

Certificate of Analysis

Laboratory Reference: 190820-080

| | | | |
|--------------------------|--|---------------------------|--------------------|
| Attention: | Operations . | Final Report: | 331963-0 |
| Client: | VEOLIA WATER | Report Issue Date: | 03-Sep-2019 |
| Address: | | Received Date: | 21-Aug-2019 |
| Client Reference: | Hawea Ponds Monthly August 2019 | Sampled By: | WLS |
| Purchase Order: | PO7300069233 | Quote Reference : | 42 |

Sample Details

WATERS

| | |
|--------------------------|----------------------------------|
| Lab Sample ID: | 190820-080-1 |
| Client Sample ID: | |
| Sample Date/Time | 20/08/2019 |
| Description: | Hawea Effluent (RM 10.308.02) |

General Testing

| | | |
|----------------------------|------|-----|
| Ammoniacal Nitrogen (as N) | mg/L | 39 |
| CBOD5 (as O2) | mg/L | 34 |
| Total Nitrogen (as N) | mg/L | 55 |
| Total Phosphorus (as P) | mg/L | 6.8 |
| Total Suspended Solids | mg/L | 55 |

Microbiology

Escherichia coli by Membrane Filtration

| | | |
|------------------|------------|-------|
| Escherichia coli | cfu/100 mL | 66000 |
|------------------|------------|-------|

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|--|------------|---------|--------------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | ISBN 0117516139 (modified) | 0.010 mg/L | All | Invercargill |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 (as O2) by Electrode | APHA (online edition) 5210 B | 2 mg/L | All | Invercargill |
| Total Nitrogen (as N) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J, 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P B, J (modified) | 0.010 mg/L | All | Invercargill |
| Total Suspended Solids by Gravimetry | APHA (online edition) 2540 D | 2.5 mg/L | All | Invercargill |

Microbiology

Escherichia coli by Membrane Filtration


| | | | | |
|------------------|--------------------------|--------------|-----|--------------|
| Escherichia coli | USEPA Method 1603 (2002) | 2 cfu/100 mL | All | Invercargill |
|------------------|--------------------------|--------------|-----|--------------|

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher. For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited.

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Tonia Bulling
KTP Signatory



Auckland

52 Aintree Ave,
PO Box 107028,
Auckland Airport
Auckland, 2150

T: (09) 539 7600
F: (09) 539 7601

Queenstown

74 Glenda Drive,
PO Box 2614
Wakatipu
Queenstown,

T: (03) 409 0559

Invercargill

142 Esk Street
PO Box 747
Invercargill, 9840

T: (03) 214 4040
F: (03) 214 4041

Certificate of Analysis

Laboratory Reference: 190919-093

| | | | |
|--------------------------|--------------------------------|---------------------------|-------------|
| Attention: | Jennifer McGirr | Final Report: | 335304-0 |
| Client: | QUEENSTOWN LAKE DISTRICT COUNC | Report Issue Date: | 27-Sep-2019 |
| Address: | PO Box 50072, Queenstown, 9348 | Received Date: | 20-Sep-2019 |
| Client Reference: | Hawea River | Sampled By: | Watercare |
| Purchase Order: | PO028787 | Quote Reference : | 10284 |

Sample Details

| | WATERS | WATERS |
|--------------------------|-------------------------|---------------------------|
| Lab Sample ID: | 190919-093-1 | 190919-093-2 |
| Client Sample ID: | | |
| Sample Date/Time | 19/09/2019 | 19/09/2019 |
| Description: | Hawea River Upstream | Hawea River Downstream |

General Testing

| | | 190919-093-1 | 190919-093-2 |
|--------------------------------------|---------|--------------|--------------|
| Ammoniacal Nitrogen (as N) | mg/L | <0.01 | <0.01 |
| CBOD5 (as O2) | mg/L | <2.0 | <2.0 |
| Dissolved Reactive Phosphorus (as P) | mg/L | <0.005 | <0.005 |
| pH (at room temp c. 20 °C) | pH unit | 7.46 | 7.51 |
| Total Nitrogen (as N) | mg/L | <0.01 | <0.01 |
| Total Oxidised Nitrogen (as N) | mg/L | 0.02 | 0.02 |
| Total Phosphorus (as P) | mg/L | <0.01 | <0.01 |
| Total Suspended Solids | mg/L | <2.5 | <2.5 |

Microbiology

Escherichia coli by MPN(Colilert-18)

| | MPN/100 mL | 190919-093-1 | 190919-093-2 |
|--------------------------------|------------|--------------|--------------|
| Escherichia coli (Colilert-18) | | <1.0 | <1.0 |

*Results marked with * are not accredited to International Accreditation New Zealand*

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)


| Analyte | Method Reference | MDL | Samples | Location |
|--|--|--------------|---------|--------------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | ISBN 0117516139 (modified) | 0.010 mg/L | All | Invercargill |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 (as O 2) by Electrode | APHA (online edition) 5210 B | 2 mg/L | All | Invercargill |
| Dissolved Reactive Phosphorus (as P) by Colorimetry/Discrete Analyser | APHA (online edition) 4500-P E | 0.005 mg/L | All | Invercargill |
| pH (at room temp c. 20 °C) by Electrode | APHA (online edition) 4500-H B (Tested beyond 15 minute APHA holding time) | 0.1 pH unit | All | Invercargill |
| Total Nitrogen (as N) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J, 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Oxidised Nitrogen (as N) by Colorimetry/Discrete Analyser | APHA (online edition) 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P B, J (modified) | 0.010 mg/L | All | Invercargill |
| Total Suspended Solids by Gravimetry | APHA (online edition) 2540 D | 2.5 mg/L | All | Invercargill |
| Microbiology | | | | |
| Escherichia coli by MPN(Colilert-18) | | | | |
| Escherichia coli (Colilert-18) | APHA (online edition) 9223 B Colilert Quantitray | 1 MPN/100 mL | All | Invercargill |
| Preparations | | | | |
| Membrane Filtration (0.45 µm) | APHA (online edition) 4500-P B (preliminary filtration) | | All | Invercargill |

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher.
For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited .

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Tonia Bulling
KTP Signatory



Auckland

52 Aintree Ave,
PO Box 107028,
Auckland Airport
Auckland, 2150

T: (09) 539 7600
F: (09) 539 7601

Queenstown

74 Glenda Drive,
PO Box 2614
Wakatipu
Queenstown,

T: (03) 409 0559

Invercargill

142 Esk Street
PO Box 747
Invercargill, 9840

T: (03) 214 4040
F: (03) 214 4041

Certificate of Analysis

Laboratory Reference: 190919-092

| | | | |
|--------------------------|---|---------------------------|--------------------|
| Attention: | Operations . | Final Report: | 335177-0 |
| Client: | VEOLIA WATER | Report Issue Date: | 26-Sep-2019 |
| Address: | | Received Date: | 20-Sep-2019 |
| Client Reference: | Hawea Ponds Monthly September 2019 | Sampled By: | WLS |
| Purchase Order: | PO118591 | Quote Reference : | 42 |

Sample Details

WATERS

| | |
|--------------------------|----------------------------------|
| Lab Sample ID: | 190919-092-1 |
| Client Sample ID: | |
| Sample Date/Time | 19/09/2019 |
| Description: | Hawea Effluent (RM 10.308.02) |

General Testing

| | | |
|----------------------------|------|-----|
| Ammoniacal Nitrogen (as N) | mg/L | 43 |
| CBOD5 (as O2) | mg/L | 34 |
| Total Nitrogen (as N) | mg/L | 110 |
| Total Phosphorus (as P) | mg/L | 7.3 |
| Total Suspended Solids | mg/L | 280 |

Microbiology

Escherichia coli by Membrane Filtration

| | | |
|------------------|------------|-------|
| Escherichia coli | cfu/100 mL | 38000 |
|------------------|------------|-------|

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|--|------------|---------|--------------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | ISBN 0117516139 (modified) | 0.010 mg/L | All | Invercargill |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 (as O2) by Electrode | APHA (online edition) 5210 B | 2 mg/L | All | Invercargill |
| Total Nitrogen (as N) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J, 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P B, J (modified) | 0.010 mg/L | All | Invercargill |
| Total Suspended Solids by Gravimetry | APHA (online edition) 2540 D | 2.5 mg/L | All | Invercargill |

Microbiology

Escherichia coli by Membrane Filtration


| | | | | |
|------------------|--------------------------|--------------|-----|--------------|
| Escherichia coli | USEPA Method 1603 (2002) | 2 cfu/100 mL | All | Invercargill |
|------------------|--------------------------|--------------|-----|--------------|

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher. For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited.

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Tonia Bulling
KTP Signatory



Auckland

52 Aintree Ave,
PO Box 107028,
Auckland Airport
Auckland, 2150

T: (09) 539 7600
F: (09) 539 7601

Queenstown

74 Glenda Drive,
PO Box 2614
Wakatipu
Queenstown,

T: (03) 409 0559

Invercargill

142 Esk Street
PO Box 747
Invercargill, 9840

T: (03) 214 4040
F: (03) 214 4041

Certificate of Analysis

Laboratory Reference: 191021-127

| | | | |
|--------------------------|---------------------------------------|---------------------------|--------------------|
| Attention: | Jennifer McGirr | Final Report: | 340497-0 |
| Client: | QUEENSTOWN LAKE DISTRICT COUNC | Report Issue Date: | 06-Nov-2019 |
| Address: | PO Box 50072, Queenstown, 9348 | Received Date: | 22-Oct-2019 |
| Client Reference: | Hawea River | Sampled By: | Watercare |
| Purchase Order: | Not Available | Quote Reference : | 10284 |

Sample Details

| | WATERS | WATERS |
|--------------------------|-------------------------|---------------------------|
| Lab Sample ID: | 191021-127-1 | 191021-127-2 |
| Client Sample ID: | | |
| Sample Date/Time | 21/10/2019 | 21/10/2019 |
| Description: | Hawea River Upstream | Hawea River Downstream |

General Testing

| | mg/L | <0.005 | 0.016 |
|--------------------------------------|---------|--------|--------|
| Ammoniacal Nitrogen (as N) | mg/L | <0.005 | 0.016 |
| CBOD5 | mg/L | 0.77 | 0.63 |
| Dissolved Reactive Phosphorus (as P) | mg/L | 0.0039 | <0.002 |
| Nitrate (as N) | mg/L | 0.03 | 0.02 |
| Nitrite (as N) | mg/L | <0.02 | <0.02 |
| pH (at room temp c. 20 °C) | pH unit | 7.7 | 7.8 |
| Total Nitrogen (as N) | mg/L | 0.036 | 0.038 |
| Total Phosphorus (as P) | mg/L | 0.004 | <0.004 |
| Total Suspended Solids | mg/L | 1.6 | <1.0 |

Microbiology

Escherichia coli by Membrane Filtration

| Escherichia coli | cfu/100 mL | <1.6 | 4.9 |
|------------------|------------|------|-----|
| Escherichia coli | cfu/100 mL | <1.6 | 4.9 |

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|--|-------------|---------|----------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Flow Analysis | APHA (online edition) 4500-NH3 H | 0.005 mg/L | All | Auckland |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 by Electrode | APHA (online edition) 5210 B (modified) | 0.5 mg/L | All | Auckland |
| Dissolved Reactive Phosphorus (as P) by Colorimetry/ Discrete Analyser | APHA (online edition) 4500-P F | 0.002 mg/L | All | Auckland |
| Nitrate (as N) by Ion Chromatography (0.45 µm Filtered) | APHA (online edition) 4110 B | 0.02 mg/L | All | Auckland |
| Nitrite (as N) by Ion Chromatography (0.45 µm Filtered) | APHA (online edition) 4110 B | 0.02 mg/L | All | Auckland |
| pH (at room temp c. 20 °C) by Electrode | APHA (online edition) 4500-H B (Tested beyond 15 minute APHA holding time) | 0.1 pH unit | All | Auckland |
| Total Nitrogen (as N) by Persulphate Digestion and Flow Analysis | APHA (online edition) 4500-P J (modified), 4500-NO3 I | 0.010 mg/L | All | Auckland |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J (modified) (Discrete Analyser) | 0.004 mg/L | All | Auckland |
| Total Suspended Solids by Gravimetry | In House based on APHA (online edition) 2540 D, E | 1 mg/L | All | Auckland |

Microbiology

Escherichia coli by Membrane Filtration

| Escherichia coli | USEPA Method 1603 | 2 cfu/100 mL | All | Auckland |
|------------------|-------------------|--------------|-----|----------|
| Escherichia coli | USEPA Method 1603 | 2 cfu/100 mL | All | Auckland |

Preparations

| Membrane Filtration (0.45 µm) | APHA (online edition) 4500-P B (preliminary filtration) | All | Auckland |
|-------------------------------|---|-----|----------|
| Membrane Filtration (0.45 µm) | APHA (online edition) 4500-P B (preliminary filtration) | All | Auckland |



*The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher.
For more information please contact the Operations Manager.*

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited .

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Chandra Sharma
KTP Signatory



Auckland

52 Aintree Ave,
PO Box 107028,
Auckland Airport
Auckland, 2150

T: (09) 539 7600
F: (09) 539 7601

Queenstown

74 Glenda Drive,
PO Box 2614
Wakatipu
Queenstown,

T: (03) 409 0559

Invercargill

142 Esk Street
PO Box 747
Invercargill, 9840

T: (03) 214 4040
F: (03) 214 4041

Certificate of Analysis

Laboratory Reference: 191021-126

| | | | |
|--------------------------|---|---------------------------|--------------------|
| Attention: | Operations . | Final Report: | 340598-0 |
| Client: | VEOLIA WATER | Report Issue Date: | 06-Nov-2019 |
| Address: | | Received Date: | 22-Oct-2019 |
| Client Reference: | Hawea Ponds Monthly October 2019 | Sampled By: | WLS |
| Purchase Order: | PO7300076673 | Quote Reference : | 42 |

Sample Details

WATERS

| | |
|--------------------------|----------------------------------|
| Lab Sample ID: | 191021-126-1 |
| Client Sample ID: | |
| Sample Date/Time | 21/10/2019 |
| Description: | Hawea Effluent (RM 10.308.02) |

General Testing

| | | |
|----------------------------|------|-----|
| Ammoniacal Nitrogen (as N) | mg/L | 42 |
| CBOD5 | mg/L | 39 |
| Total Nitrogen (as N) | mg/L | 62 |
| Total Phosphorus (as P) | mg/L | 8.0 |
| Total Suspended Solids | mg/L | 140 |

Microbiology

Escherichia coli by Membrane Filtration

| | | |
|------------------|------------|-------|
| Escherichia coli | cfu/100 mL | 31000 |
|------------------|------------|-------|

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|---|------------|---------|----------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | HMSO (1981) ISBN 0117516139 | 0.4 mg/L | All | Auckland |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 by Electrode | APHA (online edition) 5210 B (modified) | 0.5 mg/L | All | Auckland |
| Total Nitrogen (as N) by Persulphate Digestion and Flow Analysis | APHA (online edition) 4500-P J (modified), 4500-NO3 I | 0.010 mg/L | All | Auckland |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J (modified) (Discrete Analyser) | 0.004 mg/L | All | Auckland |
| Total Suspended Solids by Gravimetry | In House based on APHA (online edition) 2540 D, E | 1 mg/L | All | Auckland |

Microbiology

Escherichia coli by Membrane Filtration

| | | | | |
|------------------|-------------------|--------------|-----|----------|
| Escherichia coli | USEPA Method 1603 | 2 cfu/100 mL | All | Auckland |
|------------------|-------------------|--------------|-----|----------|

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher. For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited.

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Chandra Sharma
KTP Signatory



Auckland

52 Aintree Ave,
PO Box 107028,
Auckland Airport
Auckland, 2150

T: (09) 539 7600
F: (09) 539 7601

Queenstown

74 Glenda Drive,
PO Box 2614
Wakatipu
Queenstown,

T: (03) 409 0559

Invercargill

142 Esk Street
PO Box 747
Invercargill, 9840

T: (03) 214 4040
F: (03) 214 4041

Certificate of Analysis

Laboratory Reference: 191118-114

| | | | |
|--------------------------|---------------------------------------|---------------------------|--------------------|
| Attention: | Jennifer McGirr | Final Report: | 343142-0 |
| Client: | QUEENSTOWN LAKE DISTRICT COUNC | Report Issue Date: | 27-Nov-2019 |
| Address: | PO Box 50072, Queenstown, 9348 | Received Date: | 18-Nov-2019 |
| Client Reference: | Hawea River | Sampled By: | Watercare |
| Purchase Order: | PO028787 | Quote Reference : | 10284 |

Sample Details

| | WATERS | WATERS |
|--------------------------|-------------------------|---------------------------|
| Lab Sample ID: | 191118-114-1 | 191118-114-2 |
| Client Sample ID: | | |
| Sample Date/Time | 18/11/2019 | 18/11/2019 |
| Description: | Hawea River Upstream | Hawea River Downstream |

General Testing

| | mg/L | <0.01 | <0.01 |
|--------------------------------------|---------|-------|--------|
| Ammoniacal Nitrogen (as N) | mg/L | <2.0 | <2.0 |
| CBOD5 (as O2) | mg/L | 0.005 | <0.005 |
| Dissolved Reactive Phosphorus (as P) | mg/L | 7.52 | 7.90 |
| pH (at room temp c. 20 °C) | pH unit | 0.08 | 0.08 |
| Total Nitrogen (as N) | mg/L | 0.01 | 0.01 |
| Total Oxidised Nitrogen (as N) | mg/L | 0.02 | 0.02 |
| Total Phosphorus (as P) | mg/L | <2.5 | <2.5 |
| Total Suspended Solids | mg/L | | |

Microbiology

Escherichia coli by MPN(Colilert-18)

| Escherichia coli (Colilert-18) | MPN/100 mL | <1.0 | 1.0 |
|--------------------------------|------------|------|-----|
| | | | |

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|--|-------------|---------|--------------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | ISBN 0117516139 (modified) | 0.010 mg/L | All | Invercargill |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 (as O2) by Electrode | APHA (online edition) 5210 B | 2 mg/L | All | Invercargill |
| Dissolved Reactive Phosphorus (as P) by Colorimetry/Discrete Analyser | APHA (online edition) 4500-P E | 0.005 mg/L | All | Invercargill |
| pH (at room temp c. 20 °C) by Electrode | APHA (online edition) 4500-H B (Tested beyond 15 minute APHA holding time) | 0.1 pH unit | All | Invercargill |
| Total Nitrogen (as N) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J, 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Oxidised Nitrogen (as N) by Colorimetry/Discrete Analyser | APHA (online edition) 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P B, J (modified) | 0.010 mg/L | All | Invercargill |
| Total Suspended Solids by Gravimetry | APHA (online edition) 2540 D | 2.5 mg/L | All | Invercargill |

Microbiology

Escherichia coli by MPN(Colilert-18)

| Escherichia coli (Colilert-18) | APHA (online edition) 9223 B Colilert Quantitray | 1 MPN/100 mL | All | Invercargill |
|--------------------------------|--|--------------|-----|--------------|
| | | | | |

Preparations


| Membrane Filtration (0.45 µm) | APHA (online edition) 4500-P B (preliminary filtration) | | All | Invercargill |
|-------------------------------|---|--|-----|--------------|
| | | | | |

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher.
For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited .

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Tonia Bulling
KTP Signatory



Auckland

52 Aintree Ave,
PO Box 107028,
Auckland Airport
Auckland, 2150

T: (09) 539 7600
F: (09) 539 7601

Queenstown

74 Glenda Drive,
PO Box 2614
Wakatipu
Queenstown,

T: (03) 409 0559

Invercargill

142 Esk Street
PO Box 747
Invercargill, 9840

T: (03) 214 4040
F: (03) 214 4041

Certificate of Analysis

Laboratory Reference: 191127-191

| | | | |
|--------------------------|--|---------------------------|--------------------|
| Attention: | Operations . | Final Report: | 345233-0 |
| Client: | VEOLIA WATER | Report Issue Date: | 13-Dec-2019 |
| Address: | | Received Date: | 28-Nov-2019 |
| Client Reference: | Hawea Ponds Monthly Nov 2019 - Resample | Sampled By: | WLS |
| Purchase Order: | PO7300079228 | Quote Reference : | 42 |

Sample Details

WATERS

| | |
|--------------------------|----------------------------------|
| Lab Sample ID: | 191127-191-1 |
| Client Sample ID: | |
| Sample Date/Time | 27/11/2019 12:30 |
| Description: | Hawea Effluent (RM 10.308.02) |

General Testing

| | | |
|----------------------------|------|-----|
| Ammoniacal Nitrogen (as N) | mg/L | 50 |
| CBOD5 (as O2) | mg/L | 15 |
| Total Nitrogen (as N) | mg/L | 71 |
| Total Phosphorus (as P) | mg/L | 7.7 |
| Total Suspended Solids | mg/L | 88 |

Microbiology

Escherichia coli by Membrane Filtration

| | | |
|------------------|------------|------|
| Escherichia coli | cfu/100 mL | 3000 |
|------------------|------------|------|

Results marked with * are not accredited to International Accreditation New Zealand

Where samples have been supplied by the client they are tested as received. A dash indicates no test performed.

Reference Methods

The sample(s) referred to in this report were analysed by the following method(s)

| Analyte | Method Reference | MDL | Samples | Location |
|--|--|------------|---------|--------------|
| General Testing | | | | |
| Ammoniacal Nitrogen (as N) by Colorimetry/Discrete Analyser | ISBN 0117516139 (modified) | 0.010 mg/L | All | Invercargill |
| Carbonaceous Biochemical Oxygen Demand, CBOD5 (as O2) by Electrode | APHA (online edition) 5210 B | 2 mg/L | All | Invercargill |
| Total Nitrogen (as N) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P J, 4500-NO3 H | 0.010 mg/L | All | Invercargill |
| Total Phosphorus (as P) by Persulphate Digestion and Colorimetry/Discrete Analyser | APHA (online edition) 4500-P B, J (modified) | 0.010 mg/L | All | Invercargill |
| Total Suspended Solids by Gravimetry | APHA (online edition) 2540 D | 2.5 mg/L | All | Invercargill |

Microbiology

Escherichia coli by Membrane Filtration


| | | | | |
|------------------|--------------------------|--------------|-----|--------------|
| Escherichia coli | USEPA Method 1603 (2002) | 2 cfu/100 mL | All | Invercargill |
|------------------|--------------------------|--------------|-----|--------------|

The method detection limit (MDL) listed is the limit attainable in a relatively clean matrix. If dilutions are required for analysis the detection limit may be higher. For more information please contact the Operations Manager.

Samples, with suitable preservation and stability of analytes, will be held by the laboratory for a period of two weeks after results have been reported, unless otherwise advised by the submitter.

Watercare Laboratory Services is a division of Watercare Services Limited.

This report may not be reproduced, except in full, without the written authority of the Operations Manager.



Tonia Bulling
KTP Signatory



Auckland

52 Aintree Ave,
PO Box 107028,
Auckland Airport
Auckland, 2150

T: (09) 539 7600
F: (09) 539 7601

Queenstown

74 Glenda Drive,
PO Box 2614
Wakatipu
Queenstown,

T: (03) 409 0559

Invercargill

142 Esk Street
PO Box 747
Invercargill, 9840

T: (03) 214 4040
F: (03) 214 4041



APPENDIX D

Daily Wastewater Flow Results



| Date | Discharge to trench (m ³) | Irrigation discharge (m ³) | Total discharge (m ³) |
|------------|---------------------------------------|--|-----------------------------------|
| 1/12/2018 | 0 | 276 | 276 |
| 2/12/2018 | 0 | 283 | 283 |
| 3/12/2018 | 0 | 184 | 184 |
| 4/12/2018 | 51 | 0 | 51 |
| 5/12/2018 | 39 | 96 | 135 |
| 6/12/2018 | 0 | 99 | 99 |
| 7/12/2018 | 0 | 276 | 276 |
| 8/12/2018 | 0 | 284 | 284 |
| 9/12/2018 | 0 | 275 | 275 |
| 10/12/2018 | 0 | 285 | 285 |
| 11/12/2018 | 0 | 276 | 276 |
| 12/12/2018 | 0 | 285 | 285 |
| 13/12/2018 | 0 | 277 | 277 |
| 14/12/2018 | 11 | 283 | 294 |
| 15/12/2018 | 0 | 95 | 95 |
| 16/12/2018 | 0 | 284 | 284 |
| 17/12/2018 | 0 | 277 | 277 |
| 18/12/2018 | 0 | 282 | 282 |
| 19/12/2018 | 0 | 277 | 277 |
| 20/12/2018 | 0 | 283 | 283 |
| 21/12/2018 | 0 | 276 | 276 |
| 22/12/2018 | 0 | 285 | 285 |
| 23/12/2018 | 0 | 275 | 275 |
| 24/12/2018 | 0 | 284 | 284 |
| 25/12/2018 | 0 | 277 | 277 |
| 26/12/2018 | 0 | 282 | 282 |
| 27/12/2018 | 0 | 275 | 275 |
| 28/12/2018 | 0 | 287 | 287 |
| 29/12/2018 | 0 | 274 | 274 |
| 30/12/2018 | 0 | 283 | 283 |
| 31/12/2018 | 0 | 277 | 277 |
| 1/01/2019 | 0 | 280 | 280 |
| 2/01/2019 | 0 | 94 | 94 |
| 3/01/2019 | 0 | 275 | 275 |
| 4/01/2019 | 0 | 284 | 284 |
| 5/01/2019 | 0 | 273 | 273 |
| 6/01/2019 | 0 | 279 | 279 |
| 7/01/2019 | 52 | 122 | 174 |
| 8/01/2019 | 212 | 0 | 212 |
| 9/01/2019 | 4 | 101 | 105 |
| 10/01/2019 | 0 | 285 | 285 |
| 11/01/2019 | 0 | 278 | 278 |
| 12/01/2019 | 0 | 281 | 281 |
| 13/01/2019 | 0 | 278 | 278 |
| 14/01/2019 | 0 | 284 | 284 |
| 15/01/2019 | 0 | 275 | 275 |
| 16/01/2019 | 0 | 99 | 99 |
| 17/01/2019 | 0 | 350 | 350 |
| 18/01/2019 | 0 | 348 | 348 |
| 19/01/2019 | 0 | 356 | 356 |
| 20/01/2019 | 0 | 344 | 344 |
| 21/01/2019 | 0 | 279 | 279 |
| 22/01/2019 | 0 | 420 | 420 |



| Date | Discharge to trench (m³) | Irrigation discharge (m³) | Total discharge (m³) |
|-------------|--|---|--|
| 23/01/2019 | 0 | 348 | 348 |
| 24/01/2019 | 0 | 258 | 258 |
| 25/01/2019 | 0 | 0 | 0 |
| 26/01/2019 | 0 | 0 | 0 |
| 27/01/2019 | 0 | 0 | 0 |
| 28/01/2019 | 0 | 1 | 1 |
| 29/01/2019 | 31 | 0 | 31 |
| 30/01/2019 | 0 | 98 | 98 |
| 31/01/2019 | 0 | 351 | 351 |
| 1/02/2019 | 0 | 254 | 254 |
| 2/02/2019 | 39 | 0 | 39 |
| 3/02/2019 | 226 | 0 | 226 |
| 4/02/2019 | 97 | 0 | 97 |
| 5/02/2019 | 101 | 0 | 101 |
| 6/02/2019 | 0 | 98 | 98 |
| 7/02/2019 | 0 | 349 | 349 |
| 8/02/2019 | 0 | 349 | 349 |
| 9/02/2019 | 0 | 352 | 352 |
| 10/02/2019 | 0 | 346 | 346 |
| 11/02/2019 | 0 | 353 | 353 |
| 12/02/2019 | 0 | 11 | 11 |
| 13/02/2019 | 0 | 346 | 346 |
| 14/02/2019 | 0 | 354 | 354 |
| 15/02/2019 | 0 | 350 | 350 |
| 16/02/2019 | 0 | 350 | 350 |
| 17/02/2019 | 0 | 349 | 349 |
| 18/02/2019 | 0 | 353 | 353 |
| 19/02/2019 | 0 | 0 | 0 |
| 20/02/2019 | 0 | 301 | 301 |
| 21/02/2019 | 0 | 351 | 351 |
| 22/02/2019 | 0 | 350 | 350 |
| 23/02/2019 | 0 | 349 | 349 |
| 24/02/2019 | 0 | 349 | 349 |
| 25/02/2019 | 20 | 349 | 369 |
| 26/02/2019 | 0 | 86 | 86 |
| 27/02/2019 | 0 | 89 | 89 |
| 28/02/2019 | 0 | 347 | 347 |
| 1/03/2019 | 0 | 353 | 353 |
| 2/03/2019 | 0 | 347 | 347 |
| 3/03/2019 | 0 | 151 | 151 |
| 4/03/2019 | 0 | 0 | 0 |
| 5/03/2019 | 0 | 0 | 0 |
| 6/03/2019 | 0 | 0 | 0 |
| 7/03/2019 | 0 | 89 | 89 |
| 8/03/2019 | 0 | 163 | 163 |
| 9/03/2019 | 0 | 90 | 90 |
| 10/03/2019 | 0 | 247 | 247 |
| 11/03/2019 | 0 | 252 | 252 |
| 12/03/2019 | 0 | 247 | 247 |
| 13/03/2019 | 0 | 89 | 89 |
| 14/03/2019 | 0 | 248 | 248 |
| 15/03/2019 | 0 | 90 | 90 |
| 16/03/2019 | 0 | 293 | 293 |



| Date | Discharge to trench (m³) | Irrigation discharge (m³) | Total discharge (m³) |
|-------------|--|---|--|
| 17/03/2019 | 0 | 89 | 89 |
| 18/03/2019 | 0 | 248 | 248 |
| 19/03/2019 | 0 | 90 | 90 |
| 20/03/2019 | 0 | 161 | 161 |
| 21/03/2019 | 0 | 0 | 0 |
| 22/03/2019 | 50 | 0 | 50 |
| 23/03/2019 | 156 | 0 | 156 |
| 24/03/2019 | 13 | 87 | 100 |
| 25/03/2019 | 9 | 253 | 262 |
| 26/03/2019 | 246 | 247 | 493 |
| 27/03/2019 | 195 | 263 | 458 |
| 28/03/2019 | 0 | 90 | 90 |
| 29/03/2019 | 0 | 346 | 346 |
| 30/03/2019 | 0 | 451 | 451 |
| 31/03/2019 | 0 | 448 | 448 |
| 1/04/2019 | 0 | 437 | 437 |
| 2/04/2019 | 0 | 265 | 265 |
| 3/04/2019 | 0 | 453 | 453 |
| 4/04/2019 | 0 | 446 | 446 |
| 5/04/2019 | 0 | 452 | 452 |
| 6/04/2019 | 0 | 447 | 447 |
| 7/04/2019 | 0 | 392 | 392 |
| 8/04/2019 | 0 | 414 | 414 |
| 9/04/2019 | 0 | 320 | 320 |
| 10/04/2019 | 0 | 156 | 156 |
| 11/04/2019 | 0 | 245 | 245 |
| 12/04/2019 | 0 | 220 | 220 |
| 13/04/2019 | 0 | 221 | 221 |
| 14/04/2019 | 0 | 397 | 397 |
| 15/04/2019 | 0 | 393 | 393 |
| 16/04/2019 | 0 | 392 | 392 |
| 17/04/2019 | 0 | 394 | 394 |
| 18/04/2019 | 0 | 319 | 319 |
| 19/04/2019 | 0 | 168 | 168 |
| 20/04/2019 | 0 | 0 | 0 |
| 21/04/2019 | 0 | 0 | 0 |
| 22/04/2019 | 0 | 0 | 0 |
| 23/04/2019 | 114 | 0 | 114 |
| 24/04/2019 | 1 | 224 | 225 |
| 25/04/2019 | 0 | 400 | 400 |
| 26/04/2019 | 0 | 400 | 400 |
| 27/04/2019 | 0 | 398 | 398 |
| 28/04/2019 | 0 | 401 | 401 |
| 29/04/2019 | 239 | 266 | 505 |
| 30/04/2019 | 0 | 221 | 221 |
| 1/05/2019 | 126 | 399 | 525 |
| 2/05/2019 | 0 | 441 | 441 |
| 3/05/2019 | 0 | 598 | 598 |
| 4/05/2019 | 0 | 383 | 383 |
| 5/05/2019 | 38 | 0 | 38 |
| 6/05/2019 | 268 | 0 | 268 |
| 7/05/2019 | 238 | 0 | 238 |
| 8/05/2019 | 167 | 0 | 167 |



| Date | Discharge to trench (m ³) | Irrigation discharge (m ³) | Total discharge (m ³) |
|------------|---------------------------------------|--|-----------------------------------|
| 9/05/2019 | 238 | 0 | 238 |
| 10/05/2019 | 342 | 0 | 342 |
| 11/05/2019 | 181 | 0 | 181 |
| 12/05/2019 | 302 | 0 | 302 |
| 13/05/2019 | 501 | 0 | 501 |
| 14/05/2019 | 288 | 0 | 288 |
| 15/05/2019 | 304 | 0 | 304 |
| 16/05/2019 | 329 | 0 | 329 |
| 17/05/2019 | 268 | 0 | 268 |
| 18/05/2019 | 214 | 0 | 214 |
| 19/05/2019 | 299 | 0 | 299 |
| 20/05/2019 | 209 | 0 | 209 |
| 21/05/2019 | 223 | 0 | 223 |
| 22/05/2019 | 134 | 0 | 134 |
| 23/05/2019 | 189 | 0 | 189 |
| 24/05/2019 | 156 | 0 | 156 |
| 25/05/2019 | 117 | 0 | 117 |
| 26/05/2019 | 116 | 0 | 116 |
| 27/05/2019 | 133 | 0 | 133 |
| 28/05/2019 | 162 | 0 | 162 |
| 29/05/2019 | 126 | 0 | 126 |
| 30/05/2019 | 0 | 0 | 0 |
| 31/05/2019 | 538 | 0 | 538 |
| 1/06/2019 | 786 | 0 | 786 |
| 2/06/2019 | 491 | 0 | 491 |
| 3/06/2019 | 159 | 0 | 159 |
| 4/06/2019 | 152 | 0 | 152 |
| 5/06/2019 | 440 | 0 | 440 |
| 6/06/2019 | 584 | 0 | 584 |
| 7/06/2019 | 830 | 0 | 830 |
| 8/06/2019 | 421 | 0 | 421 |
| 9/06/2019 | 275 | 0 | 275 |
| 10/06/2019 | 371 | 0 | 371 |
| 11/06/2019 | 62 | 0 | 62 |
| 12/06/2019 | 145 | 0 | 145 |
| 13/06/2019 | 233 | 0 | 233 |
| 14/06/2019 | 211 | 0 | 211 |
| 15/06/2019 | 197 | 0 | 197 |
| 16/06/2019 | 275 | 0 | 275 |
| 17/06/2019 | 276 | 0 | 276 |
| 18/06/2019 | 146 | 0 | 146 |
| 19/06/2019 | 283 | 0 | 283 |
| 20/06/2019 | 403 | 0 | 403 |
| 21/06/2019 | 231 | 0 | 231 |
| 22/06/2019 | 403 | 0 | 403 |
| 23/06/2019 | 453 | 0 | 453 |
| 24/06/2019 | 359 | 0 | 359 |
| 25/06/2019 | 312 | 0 | 312 |
| 26/06/2019 | 350 | 0 | 350 |
| 27/06/2019 | 219 | 0 | 219 |
| 28/06/2019 | 237 | 0 | 237 |
| 29/06/2019 | 225 | 0 | 225 |
| 30/06/2019 | 361 | 0 | 361 |



| Date | Discharge to trench (m³) | Irrigation discharge (m³) | Total discharge (m³) |
|-------------|--|---|--|
| 1/07/2019 | 173 | 0 | 173 |
| 2/07/2019 | 316 | 0 | 316 |
| 3/07/2019 | 181 | 0 | 181 |
| 4/07/2019 | 252 | 0 | 252 |
| 5/07/2019 | 400 | 0 | 400 |
| 6/07/2019 | 330 | 0 | 330 |
| 7/07/2019 | 198 | 0 | 198 |
| 8/07/2019 | 328 | 0 | 328 |
| 9/07/2019 | 300 | 0 | 300 |
| 10/07/2019 | 143 | 0 | 143 |
| 11/07/2019 | 251 | 0 | 251 |
| 12/07/2019 | 369 | 0 | 369 |
| 13/07/2019 | 311 | 0 | 311 |
| 14/07/2019 | 414 | 0 | 414 |
| 15/07/2019 | 251 | 0 | 251 |
| 16/07/2019 | 367 | 0 | 367 |
| 17/07/2019 | 213 | 0 | 213 |
| 18/07/2019 | 301 | 0 | 301 |
| 19/07/2019 | 223 | 0 | 223 |
| 20/07/2019 | 226 | 0 | 226 |
| 21/07/2019 | 251 | 0 | 251 |
| 22/07/2019 | 278 | 0 | 278 |
| 23/07/2019 | 314 | 0 | 314 |
| 24/07/2019 | 310 | 0 | 310 |
| 25/07/2019 | 275 | 0 | 275 |
| 26/07/2019 | 348 | 0 | 348 |
| 27/07/2019 | 370 | 0 | 370 |
| 28/07/2019 | 336 | 0 | 336 |
| 29/07/2019 | 335 | 0 | 335 |
| 30/07/2019 | 354 | 0 | 354 |
| 31/07/2019 | 357 | 0 | 357 |
| 1/08/2019 | 321 | 0 | 321 |
| 2/08/2019 | 180 | 0 | 180 |
| 3/08/2019 | 170 | 0 | 170 |
| 4/08/2019 | 256 | 0 | 256 |
| 5/08/2019 | 134 | 0 | 134 |
| 6/08/2019 | 136 | 0 | 136 |
| 7/08/2019 | 259 | 0 | 259 |
| 8/08/2019 | 199 | 0 | 199 |
| 9/08/2019 | 162 | 0 | 162 |
| 10/08/2019 | 211 | 0 | 211 |
| 11/08/2019 | 210 | 0 | 210 |
| 12/08/2019 | 193 | 0 | 193 |
| 13/08/2019 | 174 | 0 | 174 |
| 14/08/2019 | 160 | 0 | 160 |
| 15/08/2019 | 149 | 0 | 149 |
| 16/08/2019 | 146 | 0 | 146 |
| 17/08/2019 | 114 | 0 | 114 |
| 18/08/2019 | 147 | 0 | 147 |
| 19/08/2019 | 130 | 0 | 130 |
| 20/08/2019 | 135 | 0 | 135 |
| 21/08/2019 | 154 | 0 | 154 |
| 22/08/2019 | 88 | 0 | 88 |



| Date | Discharge to trench (m ³) | Irrigation discharge (m ³) | Total discharge (m ³) |
|------------|---------------------------------------|--|-----------------------------------|
| 23/08/2019 | 946 | 0 | 946 |
| 24/08/2019 | 835 | 0 | 835 |
| 25/08/2019 | 163 | 0 | 163 |
| 26/08/2019 | 293 | 0 | 293 |
| 27/08/2019 | 512 | 0 | 512 |
| 28/08/2019 | 463 | 0 | 463 |
| 29/08/2019 | 419 | 0 | 419 |
| 30/08/2019 | 344 | 0 | 344 |
| 31/08/2019 | 259 | 0 | 259 |
| 1/09/2019 | 215 | 0 | 215 |
| 2/09/2019 | 141 | 0 | 141 |
| 3/09/2019 | 79 | 0 | 79 |
| 4/09/2019 | 63 | 0 | 63 |
| 5/09/2019 | 106 | 0 | 106 |
| 6/09/2019 | 126 | 0 | 126 |
| 7/09/2019 | 149 | 0 | 149 |
| 8/09/2019 | 192 | 0 | 192 |
| 9/09/2019 | 193 | 0 | 193 |
| 10/09/2019 | 66 | 0 | 66 |
| 11/09/2019 | 58 | 0 | 58 |
| 12/09/2019 | 95 | 0 | 95 |
| 13/09/2019 | 233 | 66 | 299 |
| 14/09/2019 | 0 | 498 | 498 |
| 15/09/2019 | 0 | 482 | 482 |
| 16/09/2019 | 0 | 544 | 544 |
| 17/09/2019 | 0 | 507 | 507 |
| 18/09/2019 | 0 | 14 | 14 |
| 19/09/2019 | 0 | 0 | 0 |
| 20/09/2019 | 0 | 225 | 225 |
| 21/09/2019 | 0 | 552 | 552 |
| 22/09/2019 | 0 | 411 | 411 |
| 23/09/2019 | 0 | 202 | 202 |
| 24/09/2019 | 0 | 332 | 332 |
| 25/09/2019 | 0 | 186 | 186 |
| 26/09/2019 | 0 | 51 | 51 |
| 27/09/2019 | 0 | 0 | 0 |
| 28/09/2019 | 11 | 0 | 11 |
| 29/09/2019 | 96 | 0 | 96 |
| 30/09/2019 | 257 | 0 | 257 |
| 1/10/2019 | 0 | 84 | 84 |
| 2/10/2019 | 0 | 431 | 431 |
| 3/10/2019 | 0 | 552 | 552 |
| 4/10/2019 | 0 | 549 | 549 |
| 5/10/2019 | 0 | 333 | 333 |
| 6/10/2019 | 0 | 308 | 308 |
| 7/10/2019 | 0 | 212 | 212 |
| 8/10/2019 | 0 | 2 | 2 |
| 9/10/2019 | 0 | 2 | 2 |
| 10/10/2019 | 0 | 2 | 2 |
| 11/10/2019 | 0 | 2 | 2 |
| 12/10/2019 | 0 | 2 | 2 |
| 13/10/2019 | 0 | 549 | 549 |
| 14/10/2019 | 0 | 535 | 535 |



| Date | Discharge to trench (m³) | Irrigation discharge (m³) | Total discharge (m³) |
|-------------|--|---|--|
| 15/10/2019 | 0 | 81 | 81 |
| 16/10/2019 | 0 | 59 | 59 |
| 17/10/2019 | 0 | 79 | 79 |
| 18/10/2019 | 0 | 409 | 409 |
| 19/10/2019 | 0 | 159 | 159 |
| 20/10/2019 | 0 | 0 | 0 |
| 21/10/2019 | 87 | 0 | 87 |
| 22/10/2019 | 189 | 0 | 189 |
| 23/10/2019 | 238 | 0 | 238 |
| 24/10/2019 | 206 | 0 | 206 |
| 25/10/2019 | 0 | 100 | 100 |
| 26/10/2019 | 0 | 552 | 552 |
| 27/10/2019 | 0 | 550 | 550 |
| 28/10/2019 | 0 | 378 | 378 |
| 29/10/2019 | 8 | 0 | 8 |
| 30/10/2019 | 43 | 0 | 43 |
| 31/10/2019 | 0 | 99 | 99 |
| 1/11/2019 | 46 | 452 | 498 |
| 2/11/2019 | 170 | 0 | 170 |
| 3/11/2019 | 211 | 0 | 211 |
| 4/11/2019 | 197 | 0 | 197 |
| 5/11/2019 | 193 | 0 | 193 |
| 6/11/2019 | 130 | 0 | 130 |
| 7/11/2019 | 0 | 110 | 110 |
| 8/11/2019 | 0 | 547 | 547 |
| 9/11/2019 | 0 | 535 | 535 |
| 10/11/2019 | 54 | 175 | 229 |
| 11/11/2019 | 190 | 0 | 190 |
| 12/11/2019 | 168 | 0 | 168 |
| 13/11/2019 | 130 | 108 | 238 |
| 14/11/2019 | 122 | 0 | 122 |
| 15/11/2019 | 225 | 77 | 302 |
| 16/11/2019 | 142 | 163 | 305 |
| 17/11/2019 | 450 | 0 | 450 |
| 18/11/2019 | 185 | 0 | 185 |
| 19/11/2019 | 293 | 0 | 293 |
| 20/11/2019 | 153 | 0 | 153 |
| 21/11/2019 | 151 | 0 | 151 |
| 22/11/2019 | 86 | 0 | 86 |
| 23/11/2019 | 186 | 97 | 283 |
| 24/11/2019 | 175 | 0 | 175 |
| 25/11/2019 | 90 | 0 | 90 |
| 26/11/2019 | 163 | 106 | 269 |
| 27/11/2019 | 153 | 173 | 326 |
| 28/11/2019 | 141 | 0 | 141 |
| 29/11/2019 | 127 | 0 | 127 |
| 30/11/2019 | 98 | 0 | 98 |



APPENDIX E

Nitrogen Mass Balance Spreadsheet



| | |
|---|-------|
| Total N _{tot} input on LTA (kg/ha) | 1,188 |
| Total N _{tot} input on LTA (kg) | 2,769 |

| | |
|------------------------------------|-------|
| Mean % NH ₄ -N in tot N | 63% |
| Ammonia Volatilisation (%) | 15 |
| Soil Loss Factor | 19.5 |
| Nitrogen Losses (kg) | 538.7 |

| | |
|--|-------|
| Total N _{tot} discharged into Trench (kg) | 2,100 |
|--|-------|

| | |
|--|-------|
| N exported (Dry Matter) kg/ha -1 st cut | 89.8 |
| N exported (Dry Matter) kg/ha -2 nd cut | 52.0 |
| N exported (Dry Matter) kg/ha -3 rd cut | 100.9 |
| N exported (Dry Matter) kg -1 st cut | 209.3 |
| N exported (Dry Matter) kg -2 nd cut | 121.1 |
| N exported (Dry Matter) kg -3 rd cut | 235.1 |

| | Yes | No |
|---------------------------------|-----|-----|
| Number days of trench discharge | 189 | 176 |
| Number days of irrigation | 182 | 183 |

| | |
|---|--------|
| Quantity WW discharged to trench (m ³) | 42,419 |
| Quantity of Tot. Nitrogen discharged to trench (kg) | 2,100 |
| Quantity WW irrigated (m ³) | 49,914 |
| Total Volume (m ³) | 92,333 |

| Date | Outlet Nitrogen conc. Average (mg/L) | Hawea WWTP Irrigation LTA (m ³) | NH ₄ -N conc. Outlet (mg/l) | Total Nitrogen applied by Irrigation (kg) | Monthly Nitrogen applied by Irrigation (kg/ha) | Monthly NH ₄ -N applied by Irrigation (kg/ha) |
|----------------|--------------------------------------|---|--|---|--|--|
| Dec-18 | 55.0 | 7,752 | 38.0 | 426.4 | 183.0 | 126.4 |
| Jan-19 | 65.0 | 6,641 | 43.0 | 431.7 | 185.3 | 122.6 |
| Feb-19 | 56.0 | 6,785 | 42.0 | 380.0 | 163.1 | 122.3 |
| Mar-19 | 52.0 | 5,432 | 38.0 | 282.5 | 121.2 | 97.9 |
| Apr-19 | 22.0 | 8,841 | 3.8 | 194.5 | 83.5 | 14.4 |
| May-19 | 27.0 | 1,821 | 13.0 | 49.2 | 21.1 | 10.2 |
| Jun-19 | 39.0 | 0 | 30.0 | 0.0 | 0.0 | 0.0 |
| Jul-19 | 46.0 | 0 | 38.0 | 2.7 | 1.2 | 0.0 |
| Aug-19 | 55.0 | 0 | 39.0 | 0.0 | 0.0 | 0.0 |
| Sep-19 | 110.0 | 4,070 | 43.0 | 447.7 | 192.1 | 75.1 |
| Oct-19 | 62.0 | 6,029 | 42.0 | 373.8 | 160.4 | 108.7 |
| Nov-19 | 71.0 | 2,543 | 50.0 | 180.6 | 77.5 | 54.6 |
| Average | 55.0 | 4,160 | 35.0 | 230.7 | 99.0 | 61.0 |



| Date | Daily Average Nitrogen applied by irrigation (kg/ha/d) | Daily Average NH4-N applied by irrigation (kg/ha/d) | Daily Median Nitrogen applied by irrigation (kg/ha/d) | Daily Median NH4-N applied by irrigation (kg/ha/d) | Hawea WWTP Trench Discharge (m ³) | Nitrogen discharged to trench (kg) |
|----------------|--|---|---|--|---|------------------------------------|
| Dec-18 | 5.9 | 4.08 | 6.54 | 4.52 | 101 | 5.6 |
| Jan-19 | 6.0 | 3.95 | 7.76 | 5.13 | 299 | 19.4 |
| Feb-19 | 5.8 | 4.37 | 8.36 | 6.27 | 483 | 27.0 |
| Mar-19 | 3.9 | 3.16 | 3.59 | 2.90 | 669 | 34.8 |
| Apr-19 | 2.8 | 0.48 | 3.36 | 0.58 | 354 | 7.8 |
| May-19 | 0.7 | 0.33 | 0.00 | 0.00 | 6,206 | 167.6 |
| Jun-19 | 0.0 | 0.00 | 0.00 | 0.00 | 9,890 | 385.7 |
| Jul-19 | 0.0 | 0.00 | 0.00 | 0.00 | 9,075 | 417.5 |
| Aug-19 | 0.0 | 0.00 | 0.00 | 0.00 | 8,062 | 443.4 |
| Sep-19 | 6.4 | 2.50 | 0.00 | 0.00 | 2,080 | 228.8 |
| Oct-19 | 5.2 | 3.51 | 2.24 | 1.51 | 771 | 47.8 |
| Nov-19 | 2.6 | 1.82 | 0.00 | 0.00 | 4,429 | 314.5 |
| Average | 3.27 | 2.0 | 2.7 | 1.7 | 3,535 | 175.0 |

| Date | NH4-N discharged to trench (kg) | NH4-N/N Tot | Nitrogen losses (SLF) (kg) |
|----------------|---------------------------------|-------------|----------------------------|
| Dec-18 | 3.8 | 69.1% | 83.0 |
| Jan-19 | 12.9 | 66.2% | 84.0 |
| Feb-19 | 20.3 | 75.0% | 73.9 |
| Mar-19 | 25.4 | 73.1% | 55.0 |
| Apr-19 | 1.3 | 17.3% | 37.8 |
| May-19 | 80.7 | 48.1% | 9.6 |
| Jun-19 | 296.7 | 76.9% | 0.0 |
| Jul-19 | 344.9 | 82.6% | 0.5 |
| Aug-19 | 314.4 | 70.9% | 0.0 |
| Sep-19 | 89.4 | 39.1% | 87.1 |
| Oct-19 | 32.4 | 67.7% | 72.7 |
| Nov-19 | 221.5 | 70.4% | 35.1 |
| Average | 120.3 | 63.0% | |



APPENDIX F

Maintenance Records



Preventative Maintenance Task Schedule

| PM Schedule | PM Description | Perform Every | Period |
|----------------|--|---------------|--------|
| QTN-HWA-R-0006 | 1 Monthly Inspection - Hawea WWTP effluent irrigation inspection | 1 | Months |
| QTN-QTN-R-0064 | 1 Monthly Inspection Maintenance - Grounds | 1 | Months |
| QTN-QTN-R-0110 | 1 Weekly Inspection/Validate - Online Analysers - Hawea WWTP | 7 | Days |
| QTN-HWA-R-0008 | 1 Weekly Inspections - Hawea WWTP | 7 | Days |
| QTN-QTN-R-0038 | 1 Yearly Compliance - Service Fire Extinguisher | 1 | Years |
| QTN-HWA-R-0002 | 1 Yearly Inspection - Hawea WWTP effluent irrigation | 1 | Years |
| QTN-QTN-R-0049 | 1 Yearly Inspection - Site Safety | 1 | Years |
| QTN-HWA-R-0003 | 1 Yearly Maintenance - Commission Hawea WWTP effluent irrigation | 1 | Years |
| QTN-HWA-R-0004 | 1 Yearly Maintenance - Decommission Hawea WWTP effluent irrigation | 1 | Years |
| QTN-WKA-R-0040 | 1 Yearly Maintenance - Hawea WWTP Ponds Aerator | 1 | Years |
| QTN-QTN-R-0003 | 2 Yearly Inspection - Electrical Panel | 2 | Years |
| QTN-HWA-R-0001 | 6 Monthly Inspection - Hawea WWTP effluent irrigation | 6 | Months |

Manual Maintenance Tasks

| Type | Date Completed | Description |
|--------|------------------|--|
| Manual | 4/02/2019 10:16 | Hawea Ponds - aerators fault 31/1/19 |
| Manual | 20/02/2019 14:30 | Hawea Ponds Repair lock on shed door Jan 2019 |
| Manual | 15/03/2019 7:30 | Hawea WWTP RTU signalling alteration 25/2/19 |
| Manual | 28/02/2019 15:42 | Hawea WWTP investigate comms fault 24/2/19 |
| Manual | 9/07/2019 8:59 | Hawea WWTP repair irrigation pump 2 - 28/2/19 |
| Manual | 15/03/2019 7:31 | Hawea WWTP Aerators check 19/2/19 |
| Manual | 18/09/2019 14:43 | Hawea WWTP Cut and Harvest March 2019 |
| Manual | 1/05/2019 12:41 | Hawea WWTP irrigation pump 2 high current 1/4/19 |
| Manual | 16/04/2019 15:54 | Hawea Ponds Replace DO probe cap Apr 2019 |
| Manual | 18/09/2019 15:15 | Hawea WWTP Cut and Harvest May 2019 |
| Manual | 31/05/2019 13:00 | Hawea Ponds - high level alarm 30/5/19 |
| Manual | 10/09/2019 14:45 | Hawea Ponds clear broom August 2019 |
| Manual | | Hawea Ponds Investigate faulty aerator August 2019 |
| Manual | 10/09/2019 14:46 | Hawea Ponds - high level alarm 21/8/19 |
| Manual | 10/09/2019 14:46 | Hawea Ponds - swale valve fault 24/8/19 |
| Manual | | Hawea WWTP irrigation no scada alarm on fault 24/10/19 |
| Manual | | Hawea WWTP low flow to irrigation alarm 21/11/19 |
| Manual | 3/12/2019 13:46 | Hawea Cut and carry Harvest Nov 2019 |



APPENDIX G

Hawea River Water Sampling Results



Hawea River sample results

Note: Sampling of the river commenced in May 2019 in response to wastewater concentration non-compliances and subsequent discussions with the ORC

| Date and Time | Ammoniacal Nitrogen mg/L | Total Nitrogen mg/L | Dissolved Reactive Phosphorus mg/L | E. coli cfu/100mL | pH | Total Oxidised N mg/L | Total Suspended Solids mg/L | BOD ₅ mg/L | Total Phosphorus mg/L |
|---|--------------------------|---------------------|------------------------------------|-------------------|------|-----------------------|-----------------------------|-----------------------|-----------------------|
| DWSNZ MAV (GV in italics) | <i>1.24</i> | | | | | | | | |
| ANZECC physicochemical (upland river) | 0.01 | 0.295 | | | | | | | |
| ANZECC toxicity 95%ile trigger level | 0.9 | | | | | | | | |
| Microbiological Guidelines - Recreational | | | | 260 | | | | | |
| Schedule 15 - ORC Regional Plan: Water for Otago. Receiving Water Group 3 | | | 0.005 | 50 | | | | | |
| Upstream Hawea River | | | | | | | | | |
| 20/05/2019 | <0.01 | 0.05 | <0.005 | <10 | 7.66 | <0.01 | <2.5 | 3 | <0.01 |
| 20/06/2019 | <0.01 | 0.06 | <0.005 | <10 | 7.55 | <0.01 | 3.4 | <2.0 | <0.01 |
| 23/07/2019 | <0.01 | 0.07 | 0.005 | <10 | 7.69 | 0.02 | <2.5 | <2.0 | <0.01 |
| 20/08/2019 | <0.01 | 0.04 | <0.005 | <10 | 7.7 | 0.02 | 3.9 | <2.0 | 0.02 |
| 19/09/2019 | <0.01 | <0.01 | <0.005 | <1.0 | 7.46 | 0.02 | <2.5 | <2.0 | <0.01 |
| 21/10/2019 | <0.005 | 0.036 | 0.0039 | <1.6 | 7.7 | 0.03 | 1.6 | 0.77 | 0.004 |
| 18/11/2019 | <0.01 | 0.08 | 0.005 | <1.0 | 7.52 | 0.01 | <2.5 | <2.0 | 0.02 |
| Downstream Hawea River | | | | | | | | | |
| 20/05/2019 | <0.01 | 0.04 | <0.005 | 10 | 7.65 | <0.01 | <2.5 | 2.9 | <0.01 |
| 20/06/2019 | <0.01 | 0.14 | 0.008 | 41 | 7.50 | <0.01 | <2.5 | <2.0 | <0.01 |
| 23/07/2019 | <0.01 | 0.08 | <0.005 | <10 | 7.67 | 0.01 | <2.5 | <2.0 | <0.01 |
| 20/08/2019 | <0.01 | 0.06 | <0.005 | <10 | 7.59 | 0.01 | <2.5 | <2.0 | <0.01 |
| 19/09/2019 | <0.01 | <0.01 | <0.005 | <1.0 | 7.51 | 0.02 | <2.5 | <2.0 | <0.01 |
| 21/10/2019 | 0.016 | 0.038 | <0.002 | 4.9 | 7.8 | 0.02 | <1.0 | 0.63 | <0.004 |
| 18/11/2019 | <0.01 | 0.08 | <0.005 | 1 | 7.9 | 0.01 | <2.5 | <2.0 | 0.02 |

Downstream samples that are highlighted red are because they are higher than the upstream sample value.



Figure G.1: Map Indicating Location of Upstream and Downstream Sampling Point



APPENDIX H

ERPRO (2019) QLDC Lake Hawea WWTP Nitrogen Reduction Implementation

QLDC

Lake Hawea WWTP

Nitrogen Reduction Implementation

Whitianga, 20/09/2019

Contents

| | | |
|--------|---------------------------------------|----|
| 1. | Report Structure | 3 |
| 2. | Executive Summary | 3 |
| 3. | Commercial Assessment..... | 3 |
| 4. | Technical Assessment of Options | 4 |
| 4.1. | Zeolite | 4 |
| 4.1.1. | Background | 4 |
| 4.1.2. | Technical Details | 5 |
| 4.1.3. | Project Costs | 6 |
| 4.2. | Ammonia Volatilisation | 6 |
| 4.2.1. | Background | 6 |
| 4.2.2. | Technical Details | 6 |
| 4.2.3. | Project Costs | 7 |
| 4.3. | Biological Nitrogen Reduction | 7 |
| 4.3.1. | Background | 7 |
| 4.3.2. | Technical Details | 8 |
| 4.3.3. | Project Costs | 8 |
| 5. | Appendix..... | 9 |
| 5.1. | Zeolite Specifications | 9 |
| 5.2. | Pump duty point | 11 |
| 5.3. | Piping set up | 12 |

1. Report Structure

Chapter 2 presents a summary and conclusions of the on site assessment of the three options for nitrogen reduction. Chapter 3 contains the commercial assessment of the three options, while Chapter 4 explains the three options including detailed test results.

2. Executive Summary

ERPRO Environmental Ltd was tasked by the Queenstown Lakes District Council (QLDC) to develop the implementation procedure to improve the nitrogen reduction capacity of the Lake Hawea wastewater treatment plant (WWTP) based on the findings delivered in the 19/08/2019 report.

The three options considered for the Nitrogen (N) reduction procedure for the WWTP were

- a) Ammonia reduction using Zeolite
- b) Ammonia volatilisation by increasing the operational pH combined with intensive mixing
- c) Biological N reduction enhancement

Based on a cost benefit analysis (Table 1) the optimum procedure to reduce the ammonia levels is by increased ammoniacal nitrogen volatilisation by raising the pond pH and forced gas stripping using part of the existing irrigation pumping station. This option is the most economical and safe procedure for reducing the increased total ammoniacal nitrogen levels safely below the RC requirements. The initial increase of the pond pH should be generated by addition of quick lime. Later in the process, naturally occurring high pH levels can be utilised for improved ammonia reduction. The required capital expense is small and chemical costs are negligible.

| Option | kg N reduced after 21 days | k\$ spent | \$/kg N reduced |
|------------------------|----------------------------|-----------|-----------------|
| External Bio-treatment | 163 | 107.0 | 657 |
| pH Increase | 144 | 17.7 | 122 |
| Zeolite | 151 | 52.6 | 349 |

Table 1: Project Summary identifying N reduction by pH increase as preferred option

Appendix 5.3 presents a conceptual set-up using the existing irrigation pump.

3. Commercial Assessment

Addition of Zeolite is a very secure procedure to reduce ammoniacal nitrogen. However minerals are only good for one treatment (waste chemical). After treatment the minerals sink to the bottom and are lost. Furthermore, in case internal biological processes are not ignited, further applications after 2 to 3 weeks would be necessary if nitrogen levels hike up again. Hence the price as quoted by Blue Pacific Minerals makes this option quite expensive.

External biological treatment is considered safe (biomass from Wanaka WWTP) but too expensive to set up.

Reduction of ammoniacal nitrogen was tested successfully and the rates identified suggest that after approximately three weeks of operation (using the existing pump set up for irrigation) RC compliance is achievable.




Chart 1: Summary Ammoniacal Concentrations in WWTP during treatment

Chart 2 below shows a commercial comparison including the parameters evaluated during the course of this assessment.




Chart 2: Summary commercial KPIs

4. Technical Assessment of Options

4.1. Zeolite

4.1.1. Background

Zeolite is of volcanic origin and is created when volcanic rock and ash layers react with alkaline ground water. The Zeolite used for the tests is a New Zealand natural product. Zeolites are well known for their high cation exchange capacity (CEC) which allows them to adsorb cations like Ammonia. As there are plenty of ions in wastewater it is better to test the efficacy of Zeolites on site. Zeolites are used in wastewater treatment applications worldwide for improvement of Nitrogen reduction tasks.

The tests that were conducted show that the Zeolites are capable of reducing approximately 2.3 g N/kg Zeolite within 2 hours of contact time. The biggest portion of the cation exchange (about 2/3 of the total capacity) happens within the first 15 minutes.

The initial treatment of the pond would need to lower the existing level of Ammonia from 40 ppm to approximately 25 ppm to achieve RC compliance. As the pond holds a total capacity of approximately 9,500 m³ of water this equates to approximately 148 kg of N which need to be removed. Given the capacity of the Zeolite this results in approximately 64 tonnes of material.

The initial application of Zeolite should only be 50% of the calculated mass, which is 30 tonnes of Zeolite. The reason being is:

- Zeolite reacts as an alkaline with wastewater, this means that Ammonia volatilisation will further improve the N reduction
- Zeolite dramatically reduces Oxygen Reduction Potential (ORP), either by increased pH or by naturally occurring processes at the surface of the minerals
- Subsequently Zeolite sparks biological processes like naturally occurring oxygenation

The above factors were identified during the tests and there is good reason to conclude that this can be replicated at full scale in the pond. We expect

- a) a reduction of levels of Ammonia by volatilisation of about 2 - 3 ppm (currently 0) without additional mixing after a few weeks of operation
- b) a reduction of the ORP to approximately 300 mV (currently 500 mV) igniting biological N reduction
- c) an increase of oxygen levels to saturation (currently 30 %)

4.1.2. Technical Details

Mixing of Zeolite is a straightforward task. The amount applied needs to be spread out evenly over the pond which is 30,000 kg per 9,500 m² or 3.2 kg per m². The material consists of a mix of small and bigger particles with the bigger particles sinking to the bottom within a few minutes and the smaller particles (less than 20 µm) staying in suspension for hours or days. Even though the water turns “milky” it will produce ample oxygen within hours due to algal activity. Small particles (5 µm and less) could remain floating in the pond for weeks. We expect that there will be no interference with the irrigation system in case this would need to be in operation any time soon. The particles which stay in suspension are too small to cause a problem with above ground irrigation equipment (cut off point for irrigators usually 100 µm).

The advantage of this application is that no capital expense is required. This is relevant as the Lake Hawea WWTP will cease its operation within the next couple of years.

Once the Zeolite is applied into the pond the capacity to adsorb cations is gone. The material sinks to the bottom and stays there for good. Other options which use Zeolite in a filter type set up were discarded due to significant capital expenses. Such set up would allow to change the filter media once it is exhausted.

The material would be sourced from Blue Pacific Minerals (BPM) which have also provided materials for many other environmental projects in NZ e.g. the restoration project lead by NIWA at Lake Okaro (Rotorua). The material would be of milled grade so that only a small amount of big particles would be allowed to sink fast. A specification sheet is attached (Appendix 5.1).

4.1.3. Project Costs

BPM have sent through costs for delivering the required grade to Lake Hawea at the nominated quantity. The costs for the total of 64 tonnes which are required to achieve a compliant effluent are:

| Item | Unit | Cost Item | Quantity | Cost Total |
|----------------------|----------|-----------|----------|------------|
| Zeolite | to | 495 | 64 | 31,680 |
| Delivery | to | 210 | 64 | 13,440 |
| Total Material | | | | 45,120 |
| Application estimate | Lump sum | 7,500 | 1 | 7,500 |
| Cost Total | | | | 52,620 |

Table 2: Project Cost Summary Zeolite Addition

The load reduction in the pond within 2 days (achievement of RC compliance level) is 144 kg N. The specific costs for 1 kg of N reduced is 366 \$/kg N.

We expect that naturally occurring N reduction processes would take over and only one application using 64 tonnes would be required. As mentioned earlier it seems preferable to apply only half of the material first and monitor the pond to check whether it comes back into action.

In case no biological activity is initiated another dose of approximately 30 tonnes would need to be administered within a fortnight (this is based on 350 g N increase per day in the pond leading to 150 kg of Zeolite requirement daily).

The same procedure would need to be applied every year as there will be no change in water chemistry of the wastewater inflow.

4.2. Ammonia Volatilisation

4.2.1. Background

Ammonia volatilisation is the process referring to stripping ammoniacal nitrogen as gas out of the water phase. This phenomenon depends on the pH of the media. The higher the pH the more ammoniacal nitrogen is in solution and can be stripped out. The process is also temperature dependent (the higher the temperature the bigger the efficacy).

Gas stripping requires an intense exchange between the outer gas phase and the media. Stirring and natural gas exchange via the pond surface is not sufficient.

We recommend to target a pH level of 9.5 as this is still a natural range for pond environments but also allows significant N stripping results.

4.2.2. Technical Details

The tests that were performed showed that at pH of 9.5 and 18 °C 1.8 g N/m³.h was eliminated when starting the procedure at 38.7 g N/m³. After 4 hours a reduction of 7.2 g N/m³ or 18.6% (stripping efficiency of 36%) was achieved.

Heavy mixing is key for effective ammoniacal stripping and the only powerful equipment available on site is the irrigation pump. The conceptual set up includes this pump as key driving force. The discharge pipe will be connected to the irrigation piping inside the pump house leading to the SW corner of the pond where a nozzle manifold creates a water droplet shower back into the pond. This droplet shower acts as water/gas exchange tool similar to a spray tower used in water treatment.

The chemical recommended for pH increase is quick lime or $\text{Ca}(\text{OH})_2$. The simple method of using caustic soda (sodium hydroxide) is technically possible and most likely the easiest application option. However, pond health requires more than just an increase of pH and the availability of di-valent ions e.g. Calcium or Magnesium is essential. Dosing of lime will not only increase pH but will also improve structure and morphology of the benthic sludge which is key for healthy pond operation.

The amount required to achieve a pH of 9.5 is approximately 1 mM. The initial dose to increase the whole pond to a pH of 9.5 is around 700 kg. Provision of 1 tonne is recommended to allow for continuing dosage to adjust the pH on an ongoing basis. Additional 100 – 125 kg a week are required to maintain pH levels.

Quick lime is a staple chemical for soil improvement in agriculture and horticulture. It can be purchased at agriculture centres and easily transported by light truck.

Dosing of the material could be as simple as sprinkling 70 – 75 g/m² (700 kg/9500m²) by hand. Alternatively dosing of lime-milk could be arranged and the aerators could be used for mixing-in the emulsion. The accuracy of the dosing activity is not that critical compared to Zeolite as the material will mix with the entire pond body by means of dispersion.

It is also important to note that an increase of pH will reduce the ORP by 59 mV per pH unit. In our case an increase by approximately 2 pH units will bring the ORP down by 120 mV. This results in an ORP at the 300 mV mark which is good to get natural N reduction going.

4.2.3. Project Costs

The lime used for the application would be the smallest expense for the project, estimated at this stage with \$ 1.50 per kg including transport or pick up. The bigger costs are the modification of the pump house to allow the pump to be used for gas stripping. The majority of the piping can be made of PVC pressure pipes, the nozzles are off the shelf 20 mm reel nozzles. Set up requires no electrical and control equipment.

| Item | Unit | Cost Item | Quantity | Cost Total |
|--------------------|--------|-----------|----------|------------|
| Pipe Modifications | ea | 11,000 | 1 | 11,000 |
| Lime | kg | 1.50 | 1,000 | 1,500 |
| Application | ea | 1,500 | 1 | 1,500 |
| Power | \$/kWh | 0.17 | 21,600 | 3,672 |
| Cost Total | | | | 17,672 |

Table 3: Project Cost Summary pH Increase / Volatilisation

The load reduced in the pond within 3 weeks (achievement of RC compliance level) is 144 kg N. The specific costs for 1 kg of N reduced is 122 \$/kg N.

4.3. Biological Nitrogen Reduction

4.3.1. Background

Biological nitrogen reduction is currently impaired at the pond due to water chemistry. This was tested again using the pond biomass and the pond water from the WWTP. To allow further inclusion of a biological option in our assessment we have conducted a paper exercise and assumed that setting up a little external plant for nitrification / ammonia reduction using biomass from the local SBR plant could achieve reduction of ammonia without addition of chemicals. A few 30 m³ PE rainwater tanks set up as simple SBRs could work as nitrification plants as well as external bio-augmentation systems (spilling nitrifiers back into the pond).

4.3.2. Technical Details

A total of 4 x 30 m³ tanks would be sufficient to process approximately 350 m³ of pond water daily. The nitrified water would get flushed back into the pond, excess sludge would also get flushed out, seeding the pond with biomass.

It is obvious that such a system requires a higher capital expense. Operational costs are moderate (seeding, maintenance and power consumption). Plant control would be based on simple timer settings. The impact should one of the tanks fail is small with regards to environmental effects which classifies this operation as low risk.

4.3.3. Project Costs

The biggest component for this option is set up and installation. No external chemicals would need to be procured.

| Item | Unit | Cost Item | Quantity | Cost Total |
|------------------------------|----------|-----------|----------|------------|
| Nitrification SBR mini tanks | ea | 23,000 | 4 | 92,000 |
| Operation incl. power | Lump sum | 15,000 | 1 | 15,00 |
| Cost Total | | | | 107,000 |

Table 4: Project Cost Summary external nitrification

The load reduced in the pond within 3 weeks (achievement of RC compliance level) is 163 kg N. The specific costs for 1 kg of N reduced is 657 \$/kg N.

5. Appendix

5.1. Zeolite Specifications



PO Box 67, Tokoroa 3444, New Zealand
Phone +64 7 885 0550 Fax +64 7 886 0024
Email info@bpmnz.co.nz Website www.bpmnz.co.nz

ZEOLITE Technical Data

PLANT

Tokoroa

DESCRIPTION

BPM Zeolite Products are produced from quality Hydrated Ca-Na-K Aluminosilicates / mordenite and clinoptilolite zeolite

**TYPICAL CHEMICAL
ANALYSIS – XRF - %**

| | | | |
|--------------------------------|-----|-------------------|-----|
| SiO ₂ | 71 | Na ₂ O | 2.0 |
| Al ₂ O ₃ | 13 | K ₂ O | 4.0 |
| Fe ₂ O ₃ | 1.2 | TiO | 0.2 |
| MgO | 0.6 | LOI | 6.5 |
| CaO | 1.5 | | |

**TYPICAL PHYSICAL
PROPERTIES**

| | |
|--------------|-----------------------------|
| Bulk density | 0.53-0.67gm/cm ³ |
| Porosity | 60% |
| Slurry pH | 8.65 (10% aq. suspension) |
| CEC | 100-120meq/100gm |
| Surface area | 120-130m ² /gm |
| Pore size | 7 Angstroms |
| Colour | Off white |

| Grade | Size Range | |
|---------|------------|------------------|
| | (mm) | Typical % within |
| Z1 DC*F | 0.5-2.0 | 95 |
| Z1 DAB | 0-1 | 99 |
| Z1 DAB+ | 0.5-1.2 | 98 |
| Z1 DBC | 1-2 | 95 |
| Z1 DBDW | 1.2-3.5 | 90 |
| Z1 DBD | 1-3 | 80 |
| Z1-DBG | 1-6 | 90 |
| Z1 DBI | 1-8 | 80 |
| Z1 DCG | 2-6 | 90 |




Analysis - Under

| Measurement Details | |
|----------------------|--------------------|
| Sample Name | Milled Z1 26/11/18 |
| SOP File Name | Zeolite.msop |
| Lab Number | 2018277/1 |
| Operator Name | rodgers |

| Measurement Details | |
|------------------------------|----------------------|
| Analysis Date Time | 7/12/2018 9:41:51 AM |
| Measurement Date Time | 7/12/2018 9:41:51 AM |
| Result Source | Measurement |


| Analysis | |
|------------------------------------|-----------------|
| Particle Name | Zeolite A |
| Particle Refractive Index | 1.446 |
| Particle Absorption Index | 0.010 |
| Dispersant Name | Water |
| Dispersant Refractive Index | 1.330 |
| Scattering Model | Mie |
| Analysis Model | General Purpose |
| Weighted Residual | 0.49 % |
| Laser Obscuration | 16.14 % |

| Result | |
|------------------------------|-------------------------|
| Concentration | 0.0183 % |
| Span | 7.718 |
| Uniformity | 2.345 |
| Specific Surface Area | 1497 m ² /kg |
| D [3,2] | 4.01 µm |
| D [4,3] | 55.7 µm |
| Dv (10) | 1.18 µm |
| Dv (50) | 20.9 µm |
| Dv (90) | 162 µm |




| Result | | | | | | | | | |
|-----------|----------------|-----------|----------------|-----------|----------------|-----------|----------------|-----------|----------------|
| Size (µm) | % Volume Under | Size (µm) | % Volume Under | Size (µm) | % Volume Under | Size (µm) | % Volume Under | Size (µm) | % Volume Under |
| 0.0500 | 0.00 | 7.80 | 31.62 | 88.0 | 80.07 | 350 | 98.37 | 1410 | 100.00 |
| 0.0600 | 0.00 | 15.6 | 44.36 | 105 | 83.34 | 420 | 99.42 | 1680 | 100.00 |
| 0.120 | 0.00 | 31.0 | 57.97 | 125 | 86.26 | 500 | 99.94 | 2000 | 100.00 |
| 0.240 | 0.00 | 37.0 | 61.66 | 149 | 88.84 | 590 | 100.00 | 2380 | 100.00 |
| 0.490 | 1.94 | 44.0 | 65.34 | 177 | 91.13 | 710 | 100.00 | 2830 | 100.00 |
| 0.980 | 8.58 | 53.0 | 69.37 | 210 | 93.23 | 840 | 100.00 | 3360 | 100.00 |
| 2.00 | 13.46 | 63.0 | 73.13 | 250 | 95.20 | 1000 | 100.00 | | |
| 3.90 | 20.52 | 74.0 | 76.56 | 300 | 97.06 | 1190 | 100.00 | | |

5.2. Pump duty point



5.3. Piping set up





Select Language ▾
Powered by  Translate

Home
Products ▾
Distributors
About Us ▾
Technical ▾
Contact Us

TEL: NZ 0800 500 484 / INT +64 9 828 3123

- Menu**
- PLUMBING CONTROL VALVES
 - APPLIANCE PROTECTION
 - RAINWATER HARVESTING
 - RURAL
 - ANKA RANGE
 - Pipe Fittings
 - Hose Nozzles
 - Hose Nozzle Service Kits
 - Hose Reel Nozzles
 - Large Hose Nozzles
 - **Small Hose Nozzles**
 - Trigger Spray Gun
 - Air Vacuum Break
 - Check Valves
 - Foot Valves
 - Hose Tails
 - Pipe Unions
 - Quick-Lock Couplings
 - Screens
 - Swivels

Small Hose Nozzles

AHN40 Large Nozzle 40mm Anka small 32mm and 25mm Hose Nozzles are designed for smaller volume washdown. Proven to be the best in their class, this compact and reliable hose nozzle is at home in any situation, and like it's big brother they can be serviced if needed.



Application

- Dairy wash-down
- Truck wash
- Yard wash-down
- Fire fighting
- Meat works
- Marine

Sales enquiries

Features & Benefits
Specifications

Specifications

Body : Glass Fibre Reinforced Nylon
O Ring : Nitrile Rubber
Nut & Bolt : 302 Stainless Steel
Threads: BSPT
 Recommended Lubricant: Rocol MX22 Silicone Grease
Maximum Working Pressure : 7 bar (700 kpa – 100 psi) @ 20°C

Product Codes Sizes Available:

| Hose Nozzles | |
|--------------|---------------|
| Code | Size |
| AHNS 20 | 20mm (3/4") |
| AHNS 25 | 25mm (1") |
| AHNS 32 | 32mm (1 1/4") |
| AHN 32 | 32mm (1 1/4") |
| AHN 40 | 40mm (1 1/2") |
| AHNT20 | Trigger 20mm |

